Institute of Aeronautics and Applied Mechanics Prospectus





Warsaw 2023/24



Institute of Aeronautics and Applied Mechanics

The history of **the Institute of Aeronautics and Applied Mechanics (IAAM)** continues the traditions of the oldest Polish institution that offers education in the field of aeronautical engineering. In the academic year 1922/1923, the Faculty of Mechanics of Warsaw University of Technology opened the Aeronautical Group, later called the Division of Aeronautical Engineering. The aeronautical study was conducted on semesters 5 to 8. Students were admitted after the so-called half-diploma, i.e. after passing the first four semesters. That was the beginning of aeronautical studies at Warsaw University of Technology for engineers of Polish aviation companies, research units and the army.

An important stage of the development of the IAAM was the erection of the Institute of Aerodynamics in 1925-1928, where theoretical and experimental work was conducted, contributing to the development of the Polish aviation industry. It was this Institute that created designs of engines and famous constructions of Polish aircrafts; their innovative and perfect design secured Warsaw University of Technology a prominent place among the world best research units dealing with aircrafts construction and design.

During the Second World War the University activity was to a great extent limited to underground education. After the Second World War, the situation of the Institute was very difficult. The building of the Institute of Aerodynamics had been burnt down, the laboratories destroyed, there was also a shortage of research and teaching staff.

1951 was a special year in the history of the Institute. Then, the University was reorganised by merging the Wawelberg-Rotwand School with Warsaw University of Technology. The Institute of Aerodynamics was dissolved and the Faculty of Aeronautics was established. Also in 1951, construction of two new buildings - of Aeronautics and of Heat Engineering, began.

In 1960, the Faculties of Mechanics and Design and of Aeronautics were merged and the Faculty of Power and Aeronautical Engineering was founded, known under this name until today. In 1970/1971, due to the intention of shutting down the Polish aviation industry, education in the field of aeronautics was suspended and the Faculty was renamed the Faculty of Mechanics and Power Engineering (FPAE). The change was temporary, though and soon the name - Faculty of Power and Aeronautical Engineering come back. In 1975, the dean of the Faculty of Power and Aeronautical Engineering, prof. Marek Dietrich submitted to the University authorities application for merging of two institutes belonging to the Faculty, namely the Institute of Applied Mechanics and the Institute of Aviation and Hydroaeromechanics. After obtaining permission, both of these relatively young institutes, established in 1970, created the Institute of Aeronautics and Applied Mechanics. However, the original divisions structure and staff assignment have been sustained. This action was aimed at preserving education in the field of aviation, as it was at risk at that time due to plans to cancel the aviation industry in Poland.

The directors of the Institute of Aeronautics and Applied Mechanics were:

- 1975 1981 prof. Brand Dietrich
- 1981 1990 prof. Jerzy Ostrowski
- 1990 1993 prof. Jacek Stupnicki
- 1993 2002 prof. Krzysztof Kedzior
- 2002 2016 prof. Krzysztof Arczewski
- 2016 2020 prof. Grzegorz Krzesinski
- 2020 2020 prof. Teresa Zielinska,

Tomasz Goezendoref-Grabowski WUT professor is the director of the Institute since 2020 Teaching and research activities of the Institute are carried out in seven divisions:

- 1. Division of Aerodynamics
- 2. Division of Automation and Aeronautical Systems
- 3. Division of Mechanics
- 4. Division of Fundamentals of Machine Design
- 5. Division of Aeroplanes and Helicopters
- 6. Division of Theory of Machines and Robots
- 7. Division of Strength of Materials and Structures

The employees of the Institute have a wide range of competences in the field of priority areas of technology of the 21st century. Research conducted in the field of aerodynamics, mechanics and design, material properties, widely understood aviation, as well as biomechanics or robotics require interdisciplinary knowledge, which is provided by the employees of the Institute. Many of the scientific staff of the Institute holds important functions in international scientific organizations as well as research and teaching associations. The Institute has an airfield located in Sieraków. The airfield is equipped with modern laboratories allowing for theoretical as well as practical work. Modern infrastructure and modernized laboratories of the Institute create a solid basis for conducting effective scientific research.

In the further part of this prospectus, the individual divisions of the Institute are presented in detail.

Division of Aerodynamics

Institute of Aeronautics and Applied Mechanics Faculty of Power and Aeronautical Engineering Warsaw University of Technology

1. Research interest

The area of research of the Division of Aerodynamics (DA) is manifold and ranges from fundamental problems of fluid mechanics and aerodynamics to various applications in aerospace, biomechanical and environmental/wind engineering. The research activities in the DA cover wide scope of investigation methodologies and techniques: theoretical, computational and experimental, usually conducted in combination.

Main research areas include:

- Computational and experimental aerodynamics of flying and ground vehicles including cars, urban aerodynamics and wing engineering
- Hydrodynamics stability and transition to turbulence (computer simulations and experiment)
- Fluids: passive and active methods for improved efficiency of transport phenomena in fluids, environmental fluid mechanics, computational fluid dynamics (FVM, h/pspectral FEM, LS-FEM), geometric/topological optimization methods in fluid mechanics and aerodynamics including optimal control of fluid/thermal phenomena, data-based and machine learning methods in fluid mechanics (emerging area)fffgffhf
- Aeroacoustics
- Development, efficient implementations and various applications of the Lattice Boltzmann methods
- Flows: internal and external compressible and flows in porous media (computer simulations and experiment), modelling and computational methods for multiphase flows, mathematical and numerical modelling of turbulent flows
- Dynamics of droplets, surface-tension driven flows, surface-fluid interactions at hydrophobic and super-hydrophobic coatings
- Thermodynamics of ice-repelling smart surfaces for multipurpose applications
- Surface waves dynamics and metamaterials
- Uncertainty quantification, robust optimization, surrogate-based optimization.

2. Research laboratories

The Aerodynamics Laboratory in IAAM is a part of the Laboratory of the Turbine Aerodynamics and Combustion (LATiS). The main LATiS' assets are:

- Variety of wind tunnels and experimental stands
- Advanced methods and data analysis
- HPC Cluster

Adjustable Turbulence Wind Tunnel (ATWT)

- Closed-loop wind tunnel with fan power 250kW, featuring two closed test sections: environmental and aeronautical.
- Wide range of velocities, 5-90 m/s (test-section dependent).

Desired turbulence level can be obtained by employing removable meshes.







Aeronautical test section:

- Test section dimensions: 0,9m x 1,25m
- Velocity: up to 90m/s
- Turbulence level below 0,1%
- Reynolds number up to 3 million



Environmental test section:

- Test section dimensions: 2,6m x 2,0m
- Velocity up to 25m/s

• Atmospheric boundary layer development length: 10m



Low Turbulence Wind Tunnel (LTWT)

Aeronautical test section:

- Dimension of test section: 0,45m x 0,65m
- Velocity up to 60m/s
- Turbulence level up to 0,2%
- Reynolds number up to 2 million



Aeronautical Wind Tunnel (AWT)

Aeronautical test section:

- Dimension of test section: $\phi = 1,16m$
- Velocity up to 40m/s
- Reynolds number up to 1 million
- 3D aircrafts & vehicles







Transonic Wind Tunnel (TWT)

- Several test sections (Length = 1m): 0,44m x 0,1m, 0,35m x 0,35m
- Velocity 0,5 2,5 Ma
- Duration of measurement: 0,5 10 s



Cascade Wind Tunnel (CWT)

Test section:

- Dimensions: 0,35m x 0,1m
- Blades in cascade: 4-8
- Velocity: 0,2 0,35 Ma

Duration of a measurement 0,5 – 10 s.

Environmental Wind Tunnel (EWT)

Test section:

- Dimensions of test section: 1m x 1m
- Velocity up to 25m/s
- Atmospheric boundary layer development length: 4m
- Fitted with an 8 x 8 low-blockage active grid (under development)



Experiments on surface wettability and icing

Several test stands e.g.:

• Measurement of static and dynamic contact angles, contact angle hysteresis



• Icing chamber for droplet interaction T

$$T_{ambient} = -30^{\circ}C \sim 25^{\circ}C; T_{surface} = -30^{\circ}C \sim 25^{\circ}C$$

- Thermocouples
- Fast thermographic camera (FLIR X6580 SC)



Experimental stand for swirling flows (Von

- Diameter of the tank: 0.5m
- Adjustable height (up to 1m)
- Can be fitted with baffles (up to 8 along the circumference)
- Propelled by two stepper motors (up to 150rpm)
- Maximum turbulent Reynolds number: c.a. 800
- Excellent optical access (allowing convenient measurements)



PIV

Kármán tank)



Water Tunnels (WT)

Test section:

- Dimension of test section: 0,1m x 15m
- Velocity: up to 15-20 cm/s



LATIS's measuring and visualization equipment



Flow field measurements - modern and diversified apparatus used for 2D and 3D flow fields: PIV, LDA, CTA.

- PIV (Particle Image Velocimetry) provided by LaVision
- 3x Stereo system, based on lasers:
 - NDYAG 200mJ @ 15Hz
 - Litron 20mJ @ 20kHz
 - 1W constant light, laser DPSS
- LDA (Laser Doppler Anemometry) provided by Dantec Dynamics
 - 1x2 components
 - 1x1 component
- CTA (Constant Temperature Anemometer) provided by Dantec Dynamics
 - mini CTA,
 - Streamline Pro + Calibration

Pressure field measurements - modern and diversified apparatus used for pressure measurements

Multi-channel piezoresistive scanners type - PressureSystems

- 350 sensors @ 1kPa
- 96 sensors
 @ 34kPa
- 96 sensors @ 1bar

Piezoresistive microsensors Kulite type

• 48 sensors + 2x National Instruments Pxi

Water manometers

- single channel
- multi-channel

Force measurements (external and internal sting type balances).

- External and sidewall balances
 - up to three force and three moment components,
 - force range 150 2kN,
 - moment range 15 200Nm,
 - Acquisition rate up to 50kHz,
- Internal (sting type balances)
 - up to 3 force and 3 moment components,
 - force range 150 1kN
 - moment range 15 50Nm
 - Acquisition rate up to 50kHz

Fast imaging, 3D printing and software

Thermographic fast camera Flir X6580sc

• Max 4500fps

• Temperature range -50°C ~ 350°C

Fast cameras

• Photron SA-Z, SA-5, SA-1 up to 2,5 M fps

3D printers, 3D scanners, CNC workshop

Software: MATLAB, Ansys, Tecplot, Siemens NX, Lab View.

3. Key research projects

1. 2014-2019 NCBR INNOLOT "Zaawansowany zespół turbiny niskiego ciśnienia o podwyższonej sprawności" (Advanced low-pressure turbine with improved efficiency), dr inż. Jerzy Majewski

The main objectives were as follows:

- A) Virtual modelling and improvement of low pressure turbine (LPT) performance
- development/improvement of LPT unsteady flow simulation technique and comparison of numerical results with experiment,
- aerodynamic optimization of shapes of LPT sealing cavities.
- B) Experimental modeling of LPT module
- development of advanced instrumentation strategy and verification of the strategy on experiments by AvioPolska and WUT,
- development of data reduction system and validation of the technique on benchmark cases defined by AvioPolska.
- 2014-2016 NCBR GEKON "Opracowanie i wdrożenie technologii Małych Elektrowni Wiatrowych o mocach 5kW i 10kW" (Design and technological implementation of Small Wind Turbines with the power of 5kW and 10kW), prof. Jacek Szumbarski

This project aimed at development of highly-efficient small 5kW and 10 kW HAVTs. The role of the DA's teams was to design and optimize the rotors (with special emphasis on self-starting capabilities) and experimental evaluation of obtained performance).

 2019-2020 NCBR GOSPOSTRATEG "Potencjał rozwoju i wdrażania w Polsce technologii kolei próżniowej w kontekście społecznym, technicznym, ekonomicznym i prawnym" (Potential for the development and implementation of vacuum tube high-speed train technology in Poland in the social, technical, economic and legal context), HYPERLOOP, prof. Janusz Piechna.

During realization of this project the concept of an unconventional implementation of a Low Pressure Tube Transport (LPTT) system for a network with station-to-station distances of 300 km, based on the use of circular tunnels in which modular vehicles consisting of three interconnected functional segments move on wheels with airless tires, was proposed. The physical limitations associated with high-speed vehicle travel in tunnels have been taken into account. The reasons for the expected inconvenience in the travel system, compensated by

short travel times, were justified. Assumptions for the use of locomotion, safety, and passenger segments in the construction of a vacuum modular vehicle were considered, as well as systems to ensure the efficient conversion of serial traffic in tunnels to parallel traffic in station areas. Schemes of station construction and traffic organization in the station area were presented, as well as assumptions for a number of systems increasing the safety of vehicle traffic used in emergency situations. Visualizations of some solutions were shown. To check the proposed constructions and organization, two travel simulators of this railroad were built for the presented LPTT system, a mechanical and a virtual simulator. The mechanical simulator took into account the characteristic features and solutions of the passenger module. The virtual simulator additionally provided visualizations of the parts of the station available to passengers.



Platform seen in virtual simulator (left), cockpit of mechanical simulator (right).

4. 2015-2019 NCBR PBS 3 "Aktywny system tłumienia drgań pojazdu" (The active system of car body oscillation damping), prof. Janusz Piechna.

Investigation made in this project was concentrated on the different aspects of the car aerodynamics. In the case of road cars, road safety is the primary factor. The geometry of high-speed road cars has no regulatory restrictions. In addition to the high engine power and effective shape, they can use various types of additional movable aerodynamic elements to adjust their aerodynamic characteristics to the road conditions. Based on the geometry of a two-seater prototype of such a vehicle, a numerical analysis of the influence of a number of additional movable aerodynamic elements on its aerodynamic characteristics was performed. Several of them were installed on the prototype. An electronic system recording a number of motion parameters of the entire car body and some of its movable elements installed on the body was designed and built. The system has been adapted to program the motion of additional aerodynamic elements according to the set algorithms of their activation, temporarily changing the aerodynamic characteristics of the car. An experimental study of the effect of changes in the aerodynamic characteristics of the prototype on its dynamic properties during a drive through a test road section was carried out. It was shown to what extent an average driver can increase the safe speed of the curve of the road using the possibilities of moving aerodynamic elements installed on it.

The simulations of the behavior of a car equipped with a movable wing during braking, while negotiating a curve, have been performed. At the outset, it was assumed that the vehicle is traveling at high speed on a curve of the road and there is a need for sudden braking. Two cases were analyzed. In the first, the vehicle brakes, but the rear wing is stationary. In the second, the vehicle brakes, but the rear wing changes its angle of alignment increasing aerodynamic downforce (negative lift) and aerodynamic drag. The differences in the behavior of the vehicle in the two cases were presented. The numerical model built consisted of a vehicle dynamics model (ADAMS), taking into account the action of inertial forces occurring on its moving components, coupled with an aerodynamic model (ANSYS-Fluent), allowing to calculate the instantaneous values of aerodynamic forces caused by dynamic changes in the position of the vehicle body with a flexible suspension and the rear fixed or moving wing. The motion of the vehicle relative to a stationary reference system - the road surface - was simulated. It was shown that when braking is required while driving on a curve of the road, activation of the movable wing results in stabilization of the vehicle's motion comparable to the action of the mechatronic ESP system.



Photographs of the vehicle prepared for passage in two different configurations. Asymmetrically inclined wing for cornering configuration (**left**) and braking configuration (**right**).



Pressure coefficient for the inlet speed of 20 m/s. On the (left), circulation fans generating air curtains were deactivated; on the (right)—they were active.

5. 2017-2020 NCN OPUS 11 "Statystyczne modelowanie dwu-składnikowych przepływów turbulentnych z powierzchniami rozdziału" (Statistical modelling of two-phase turbulent flows with sharp interfaces), dr inż. Tomasz Wacławczyk.

The main aim of this project was to design the physical/mathematical and numerical framework for efficient implementation of the turbulence models designed for numerical simulation of the turbulent two-phase flow. To this goal, the new modeling approach based on conditional averaging and closure of the unknown parameters by the conservative model was introduced [A]. The proposed solution allows to model interaction of the sharp interface between the two-phases with turbulent velocity field similarly to the phase transition. In the new statistical model of the interphase region, the interphase region evolution is depended on the local properties of the flow field (characteristic length and/or time scales). The results of this new approach are presented in the figure from work [C].



The top row depicts advection of the gas bubble in equilibrium case (without interaction with turbulent velocity field) the bottom row presents bubble which trajectory is affected due to presence of turbulent eddy with the known characteristic length scale. One can observe how presence of the turbulent eddy affects the local thickness of the interphase region that is statistical (ensemble averaged) representation of the sharp interface affected by stochastic, turbulent velocity field.

The main outcome of the project can be found in three publications:

[A] T. Wacławczyk, On a relation between the volume of fluid, level-set and phase field interface models, International Journal of Multiphase Flow, vol. 97, 2017, pp. 60–67 [B] T. Wacławczyk, Modeling of non-equilibrium effects in intermittency region between two-phases, International Journal of Multiphase Flow, vol. 134 , 2021, pp. 1–20 [C] T. Wacławczyk, On differences between deterministic and statistical models of the mesoscopic intermittency region, Acta Mechanica Sinica, vol. 38, 2022, 722045.

 2019-2022 NCN PRELUDIUM 15 "Stabilność hydrodynamiczna oraz intensyfikacja mieszania laminarnego w kanale poprzecznie pofalowanym do przepływu" (Hydrodynamic stability and laminar mixing enhancement in a transversely corrugated channel), dr inż. Nikesh. The main goal of this project was to explore the potential of natural instabilities in internal (channel) flows invoked by transversely-oriented wall corrugation for intensification of laminar mixing. In particular, various form of parametrized wall corrugations have been considered and optimized to minimize the critical Reynolds number while keeping hydraulic penalty as law as possible. Wide range of corrugation amplitudes and geometric periods has been considered leading to broad picture of possibilities of mixing enhancement.

7. 2019-2023 NCN OPUS 16 "Opracowanie i implementacja nowej metody modelowania przejścia laminarno - turbulentnego w warstwie przyściennej uwzględniającej utratę stabilności przepływu na skutek oddziaływania fal akustycznych", (New modelling method for the laminar-turbulent transition in a boundary layer under interaction with acoustic waves), prof. Sławomir Kubacki

The proposed project aimed at reducing the computational costs necessary to simulate the coupling of acoustics and boundary layer flow. It was believed that simulating simultaneously hydrodynamic instabilities and acoustic waves within a single CFD URANS solver was a right approach for achieving the main goals of the project. The main objectives of the project were:

- Understanding the instability mechanism in the laminar and turbulent boundary layers triggered by the acoustic waves (direct numerical simulations and experiments);
- Formulation of guidelines, based on the collected DNS data, for closure of the unknow terms in the exact form of the Reynolds-stress transport and/or the laminar/turbulent kinetic energy equations;
- Development and testing of 3D URANS/hybrid RANS-LES aero-acoustics simulation/coupling strategies.



Left: Schematic of the test section and loudspeaker location, Right: power spectra density spectra at the test section outlet.

7. 2020-2024 NCN PRELUDIUM 18 "Dynamika granicy trójfazowej dla przepływów inercyjnych" (Triple line dynamics in inertial flows), dr inż. Michał Remer.

The main objective of the project is to investigate the dynamics of the interface in high velocity regime, where inertia forces cannot be neglected. The Weber number is a measure of the importance of the fluid's inertia over its surface tension, which might be useful parameter for inertia impact on θ_d during modelling. The main goal of the research is to

determine physical relationship between the dynamic apparent contact angle θ_d and the velocity of the triple line V for dynamically moving triple line. This goal can be obtained by extending assumptions of Kistler/Shikhmurzaev model. High velocity range of the triple line is considered – for the capillary flows in tubes for the droplet impingement time dependent flows in capillary tubes (accelerated, decelerated). Kistler model describes accurately θ_d in case of hydrophilic surfaces in low range of Ca number. When wettability is altered the Kistler model seems to become invalid. This project will concern wide range of surface wettability level. Phenomenon of the dynamic interaction a water droplet with any surface is essential in many industrial applications such as ink printing, coating, anti-icing or internal flows. Some of them require high level of wettability while others require easiness of the water repel. Recent development allows to design and manufacture surfaces characterised by wide range of the macroscopic contact angle. Parameter θ_0 is not enough to set explicit statement which type of the droplet impact or the flow scenario will take place. On the other hand, relation between the dynamic contact angle θ_d and the velocity of the triple line V is the most crucial parameter, decisive about scenario of the flow. Also the rate of change of mentioned relation seems to be very important. Despite the fact that, there exist several models for $\theta_d(V)$ relation, the most commonly used of them - Kistler and Shikhmurzaev models, they are not taking into account inertia effects. Nowadays, it is more accessible to conduct numerical simulations of the multiphase flows, hence it is extremely important to state models which can give results that maximally approximate the reality.

8. 2020-2025 NCN SONATA 15 "Od niestabilności hydrodynamicznej do chaotycznej adwekcji i mieszania w przepływach laminarnych", (From hydrodynamic instability to chaotic advection and laminar mixing), dr inż. Stanisław Gepner.

The intention of the proposed project is to study flow dynamics and various hydrodynamic instability mechanisms in the case of flow through a channel whose walls are subject to geometric modifications in the form of large-scale corrugations. The research tasks planned in the project will be based on methods of hydrodynamic stability theory, methods adopted from theory of dynamical systems and used for characterization and onset of chaotic advection. The problem of mixing quantification will be approached from the perspective of stirring (intensification of mechanical mixing) in the Lagrangian framework, via investigation of strange eigen modes of the advection-diffusion operator used to estimate upper limits on the rate of mixing and via the classical norm-based approach.

The experimental part of the project will make use of currently available infrastructure and equipment purchased or manufactured in the scope of the proposed project. Flow measurements will be performed using particle image velocimetry (PIV), laser Doppler anemometry (LDA) and fluorescent dye visualization techniques. The experimental set-up is 3D printed and later CNC machined. It is planned to use materials that have same refraction coefficient as the working fluid (e.g.: glycerine and glass) to allow for visual measurements that are free of optical distortion.

The results of the project will significantly contribute to the development of knowledge in hydrodynamic stability, particularly in the field of linear and nonlinear stability theory of laminar internal flows. The implementation of the project will also contribute to the development of methods for analysing the efficiency of mixing processes in laminar flows, primarily by developing new or appropriate adaptations of existing quantitative criteria/measures. Despite the purely basic nature of the research, the results of the project will shed light on future developments in laminar mixing technology and equipment.



Experimental setup during PIV measurements (left) and main flow features past the bifurcation point (right)

9. 2021-2023 NCN POLS (Norwegian Fundings) "Badanie wielkoskalowych struktur w turbulentnym wirowym przepływie von Kármána z przegrodami" (Investigation of large structures in the von Karman swirling flow), dr inż. Paweł Baj.

The project aims to explore the properties of turbulent von Karman swirling flow (VK flow). This flow is canonical in turbulence research and can be briefly described as flow within a vessel closed from both sides with impellers spinning in opposite directions. The project focuses on a recently observed low-frequency, large-scale motion (LSM) present in such a configuration. This feature is the strongest close to the vessel centre, where it accounts for more than half of the turbulence energy, and weakens progressively away from the centre. An experimental facility, suitable for the particular conditions of the project, was designed, built and equipped. In particular, it allows for the application of Particle Image Velocimetry, which is the primary experimental technique used within the project.

The research goals are to address the following four questions considering the studied flow feature: (i) is this phenomenon reproducible in different facilities, (ii) how sensitive is it to the history of the flow, (iii) how sensitive is it to the geometry of the vessel, (iv) can it be controlled via different stirring strategies. Two main stirring approaches are considered here, modulated stirring and random stirring.



Schematic of the von Karman flow (left), the experimental facility - PIV measurements (central), contours of velocity fluctuations energy associated with the LSM (right).

10. 2021-2024 NCN SONATA 16 "Bathymetry designs in water waves systems - is nature more efficient than a human?", dr inż. Tomasz Bobiński.

Nature is probably the main source of inspiration for scientists. Deep understanding of patterns observed in surrounding environment can lead to better designs of products and constructions. The reason for this is the fact that evolution is typically producing the optimized response to external conditions. Chicken bone, having optimized external shape and internal architecture with respect to minimum weight and maximum strength, is one of the examples. Shape adaptation is also visible in case of trees. Depending on the wind loading, the optimal shape of tree's cross-section might be provided by adaptive growth that fairly distributes the load (axiom of uniform stress)- there are no zones with locally excessive stresses nor regions not fully loaded. The evolution of shape can be observed in multiple natural systems. One of them is meandering river, which has attracted the world's greatest thinkers. Morphodynamics of this type of systems is governed by the interaction between erodible walls and sediment-carrying fluid. River bed can be mobilized by a shear stress exerted onto the bed by water flow. When the flow carries large quantity of sediment then abrasion can enhance this effect. The magnitude of shear stress is governed by local water velocity. River shape is slowly evolving in time together with the flow and bottom topography. Curvature of the river shape is altering the flow in such a way that there are regions characterized by higher velocity, where the sediment is flushed away resulting in locally larger depth. In the regions, where the flow is slower the depth is smaller. This process renders typically smoothly varying bathymetry. In this research project we focus on the propagation of surface water waves in such system. From the viewpoint of surface waves, meandering river can be considered as a waveguide with spatially varying refractive index that depends on local water depth. By varying water depth one can alter the propagation of waves. Meanders of the waveguide can be considered as waveguide defects that enhance scattering of waves compared to a straight waveguide. Through proper design of bottom topography one can render these defects invisible to the incident waves can be perfectly transmitted despite the defects. Remarkably, bathymetry rendered by fluvial processes in meandering river is very similar to a specially designed bed that hides/cloaks defects of a meandering waveguide. The main objective of this research project is to answer the question whether natural changes occurring in bottom topography of meandering rivers can enhance transmitted energy flux with respect to surface water waves, and how this enhancement compares with human-designed bathymetry, or in other words, can human be more efficient? Can we learn from nature? To answer this question we will compare propagation of surface water waves in different waveguide geometries with bathymetries

that were specially designed to hide the defects and bathymetries generated "naturally" by the flow. The project includes performing experiments and numerical simulations.



Top: Experimental setup. Bottom: the wavepacket temporal evolution within two waveguides: (i) with flat bottom and (ii) cloaking bathymetry (designed through conformal mapping).

11. 2022-2026 NCN OPUS 21 "Wpływ gradientu ciśnienia i przepływu dużej skali na przejście do turbulencji" (Effect of pressure gradient and large-scale-flow on transition to turbulence), dr inż. Łukasz Klotz.

Turbulence is a ubiquitous phenomenon commonly encountered in nature and in engineering applications, ranging from geophysical flows to flows around an airplane wing or within industrial pipelines. From an experimental perspective, turbulence is advected by the bulk flow that flushes away turbulence out of the test section and, as a result, only finite time observations are possible. One possibility to solve this problem is to create the base flow with zero mean bulk velocity to keep the turbulent structures stationary in space and study their dynamics for an arbitrarily long time. During this project, two different experimental techniques will be used. With flow visualizations, turbulent and laminar regions will be optically detected and characterized statistically. With Particle Image Velocimetry (PIV), velocity fields will be measured to gain additional information about the dynamics of typical turbulent structures.

Selected projects funded by EU

- 2009-2012 EU Project, SCP7-GA-2008-218626, FLOWHEAD "Fluid Optimisation Workflows for Highly Effective Automotive Development Processes", prof. Jacek Rokicki.
- 2010-2014 EU Project, FP7-AAT-2010-265780, IDIHOM "Industrialisation of High-Order Methods Top-Down Approach", prof. Jacek Rokicki.
- 2011-2016, EU Project, ESPOSA "*E*fficient Systems and Propulsion form Small Aircrafts" project coordinator at WUT Prof. Z Goraj, project coordinators at Division of Aerodynamics: prof. J. Rokicki, prof. Slawomir Kubacki.
- 2013-2016 EU Project, FP7-AAT-2013-RTD-1, UMRIDA "Uncertainty Management for Robust Industrial Design in Aeronautics", prof. Jacek Rokicki, prof. Jacek Szumbarski.

Selected commercial projects

- 2019-2021 "Wykonanie badań eksperymentalnych wyznaczających oddziaływanie wiatru na elewację i konstrukcję budynku wieżowego BELLONA TOWER o zwiększonej wysokości do 175m i zmienionym kształcie budynku oraz wpływ budynku na komfort użytkowników tego budynku, zlokalizowanego przy ul. Grzybowskiej w Dzielnicy Śródmieście m.st. Warszawy" dla Projekt Polsko Belgijska Pracownia Architektoniczna Sp. z o.o., prof. Jacek Szumbarski. English: Experimental determination of the wind loads on the building BELLONA TOWER (175 m) and its impact on the pedestrian's comfort.
- 2. 2019-2022 "Wykonanie badań eksperymentalnych wyznaczających oddziaływanie wiatru na elewacje i konstrukcję budynku wieżowego CHOPIN TOWER o wysokości H =126m, oraz wpływ budynku na komfort wiatrowy przechodniów w jego otoczeniu i komfort użytkowników tego budynku, zlokalizowanego przy ul. Wroniej (róg Grzybowskiej) w Dzielnicy Śródmieście m.st. Warszawy" dla Projekt Polsko Belgijska Pracownia Architektoniczna Sp. z o.o., prof. dr hab. inż. Jacek Szumbarski.

English: Experimental determination of the wind loads on the building CHOPIN TOWER (126 m) and its impact on the pedestrian's comfort.

- 2022 "Badania aerodynamiczne kolarzy torowych wraz z opisem wyników" dla Polskiego Komitetu Olimpijskiego, mgr inż. Bartosz Olszański.
 English: Aerodynamic investigations of race track cyclists (ordered by Polish Olympic Committee).
- 4. Since 2016 commercial research for PHILIPS division of R&D of the street lamps oriented on aerodynamic loads measurements. The aim of research is measuring aerodynamic forces on lamps and resistance on high velocity up to 140km/h
- 5. 2017-2018 commercial research for Institute of Aviation in Warsaw, of the gyrocopter oriented on the aerodynamic characteristics measurements. The aim of research was to find the influence of elements like the landing gear and the stabilizer setups.

4. Relevant achievements

- Piechna J., Kurec K., Remer M. et al.: Układ do tłumienia drgań nadwozia pojazdu w czasie szybkiej jazdy i tylny płat dociskowy z aktywnymi elementami aerodynamicznymi, Wynalazek, Numer zgłoszenia (w pierwszym kraju zgłoszenia powyżej): P.426981, Numer patentu/prawa: PL 239050.
 English: Vibration damping system for vehicle body during high-speed driving and rear pressure wing with active aerodynamic elements. Invention, Application number (in the first country of filing above): P.426981, Patent/Right Number: PL 239050.
- Piechna J., Laube T., Piechna A.: Rotacyjny naddźwiękowy silnik cieplny z komorą spalania z wirującą falą detonacyjną o zwiększonej sprawności , Wynalazek, Numer zgłoszenia (w pierwszym kraju zgłoszenia powyżej): P.430727, Numer patentu/prawa: PL 238626 English: Rotary supersonic combustion chamber heat engine with rotating

detonation wave with increased efficiency. Invention, Patent/Right Number PL 238626

- Piechna J., Kindracki J., Piechna A. et al.: Rotacyjny naddźwiękowy silnik cieplny z komorą spalania z wirującą falą detonacyjną, Wynalazek, Numer zgłoszenia (w pierwszym kraju zgłoszenia powyżej): P.430728, Numer patentu/prawa: PL 238627 English: Rotary supersonic combustion chamber heat engine with rotating detonation wave. Invention, patent/right PL 238627.
- Piechna J.: Uszczelnienie nośnej poduszki gazowej pojazdu kolei próżniowej, Wynalazek, Numer zgłoszenia (w pierwszym kraju zgłoszenia powyżej): P.425924, Numer patentu/prawa: PL 236112 English: Sealing of the carrier gas bag of a vacuum railway vehicle. Invention, patent/right PL 236112.
- 5. Mueller N., Piechna J., Sun G. [i in.]: Wave disc engine apparatus , Invention, Number patent/right: US 9856791
- 6. WUT Rector's 1st-degree team award for scientific achievements in 2021 for prof. J. Piechna and dr M. Remer.
- 7. In 2021, Dr. Tomasz Wacławczyk was awarded the Scientist of the Future award by the chapter of the Intelligent Development Forum (FIR). During the conference, FIR presented its work on modeling multiphase flows in the context of their use in industry.

5. Selected relevant publications

 Kurec Krzysztof, Olszański Bartosz, Gumowski Konrad, Klamka Michał, Remer Michał, Piechna Janusz, Kubacki Sławomir: Air curtain as a SARS-CoV-2 spreading mitigation method in a small aircraft cabin, Proceedings of the Institution of Mechanical Engineers Part G-Journal of Aerospace Engineering, SAGE Publications, 2023, s. 1-25, DOI:10.1177/09544100231153703

- Broniszewski Jakub, Piechna Janusz: Fluid-Structure Interaction Analysis of a Competitive Car during Brake-in-Turn Manoeuvre, Energies, vol. 15, 2022, s. 1-16, DOI:10.3390/en15082917
- Piechna Janusz, Kurec Krzysztof, Broniszewski Jakub, Remer Michał, Piechna Adam, Kamieniecki Konrad, Bibik Przemysław: Influence of the Car Movable Aerodynamic Elements on Fast Road Car Cornering, Energies, vol. 15, nr 3, 2022, s. 1-28, DOI:10.3390/en15030689
- 4. Piechna Janusz: **A Review of Shock Wave Compression Rotary Engine Projects**, Energies, vol. 15,2022, s. 1-35, DOI:10.3390/en15249353
- Gałecki Jakub, Szumbarski Jacek: Adjoint-based optimal control of unsteady incompressible flows with concvective-like energy-stable open boundary conditions, Computers & Mathematics With Applications, vol. 106, 2022, s. 40-56, DOI:10.1016/j.camwa.2021.12.004
- Kurec Krzysztof, Olszański Bartosz, Gumowski Konrad, Klamka Michał, Remer Michał, Piechna Janusz, Kubacki Sławomir: Air curtain as a SARS-CoV-2 spreading mitigation method in a small aircraft cabin, Proceedings of the Institution of Mechanical Engineers Part G-Journal of Aerospace Engineering, SAGE Publications, 2023, s. 1-25, DOI:10.1177/09544100231153703
- Klotz Łukasz, Lemoult Grégoire, Avila Kerstin, Hof Björn: Phase Transition to Turbulence in Spatially Extended Shear Flows, Physical Review Letters, American Physical Society, vol. 128, nr 1, 2022, s. 1-5, DOI:10.1103/physrevlett.128.014502
- Di Vaira Nathan J., Łaniewski-Wołłk Łukasz, Johnson Jr. Raymond L., Aminossadati Saiied M., Leonardi Christopher R.: Influence of particle polydispersity on bulk migration and size segregation in channel flows, Journal of Fluid Mechanics, vol. 939, 2022, s. 1-32, DOI: 10.1017/jfm.2022.166
- Gruszczyński Grzegorz, Łaniewski-Wołłk Łukasz: A comparative study of 3D cumulant and central moments lattice Boltzmann schemes with interpolated boundary conditions for the simulation of thermal flows in high Prandtl number regime, International Journal of Heat and Mass Transfer, vol. 197, 2022, s. 1-16, DOI:10.1016/j.ijheatmasstransfer.2022.123259
- Yadav Nikesh, Gepner Stanisław: Slowing down convective instabilities in corrugated Couette Poiseuille flow, Journal of Fluid Mechanics, nr 950, 2022, s. 1-28, DOI:10.1017/jfm.2022.805
- Baj Paweł, Portela F. Alves, Carter D.W.: On the simultaneous cascades of energy, helicity, and enstrophy in incompressible homogeneous turbulence, Journal of Fluid Mechanics, vol. 952, 2022, s. 1-28, DOI:10.1017/jfm.2022.912
- 12. Gepner Stanisław, Yadav Nikesh, Szumbarski Jacek: **Secondary flows in a longitudinally** grooved channel and enhancement of diffusive transport, International Journal of Heat and Mass Transfer, 2020, vol. 153, s.1-11. DOI:10.1016/j.ijheatmasstransfer.2020.119523
- Gepner Stanisław, Floryan J.M. : Use of Surface Corrugations for Energy-Efficient Chaotic Stirring in Low Reynolds Number Flows, Scientific Reports, 2020, vol. 10, nr 1, s.1-8, Numer artykułu:9865. DOI:10.1038/s41598-020-66800-5

- 14. Kizilova Natalya, Sauermoser M., Kjelstrup S. [i in.]: Fractal-like flow-fields with minimum entropy production for polymer electrolyte membrane fuel cells, Entropy, 2020, vol. 22, nr 176, s.1-23. DOI:10.3390/e22020176
- 15. Sauermoser M., Pollet B.G., Kizilova Natalya [i in.]: Scaling factors for channel width variations in treelike flow field patterns for polymer electrolyte membrane fuel cells An experimental study, International Journal of Hydrogen Energy, 2021, vol. 46, s.1-15. DOI:10.1016/j.ijhydene.2021.03.102
- 16. Liu T., Semin B., Klotz Łukasz [i in.]: Decay of streaks and rolls in plane Couette– Poiseuille flow, Journal of Fluid Mechanics, 2021, vol. 915, s.1-21. DOI:10.1017/jfm.2021.89
- Klotz Łukasz, Pavlenko A. M., Wesfreid J.E.: Experimental measurements in plane Couette–Poiseuille flow: dynamics of the large- and small-scale flow, Journal of Fluid Mechanics, 2021, vol. 912, nr A24, s.1-31. DOI:10.1017/jfm.2020.1089
- Marchlewski Krzysztof, Łaniewski-Wołłk Łukasz, Kubacki Sławomir: Aerodynamic Shape Optimization of a Gas Turbine Engine Air-Delivery Duct, Journal of Aerospace Engineering, 2020, vol. 33, nr 4, s.1-12. DOI:10.1061/(ASCE)AS.1943-5525.0001157
- Rarata Zbigniew, Dacko Adam, Polak Szymon [i in.]: Vibro-acoustic response of spacecraft instrument subjected to diffuse sound field: Numerical simulations and experimental verification, Applied Acoustics, 2021, vol. 184, s.1-14. DOI:10.1016/j.apacoust.2021.108338
- 20. Wacławczyk Tomasz: Modeling of non-equilibrium effects in intermittency region between two-phases, International Journal of Multiphase Flow, 2021, vol. 134, s.1-20. DOI:10.1016/j.ijmultiphaseflow.2020.103459

Aircraft Design Division

Institute of Aeronautics and Applied Mechanics Faculty of Power and Aeronautical Engineering Warsaw University of Technology

Research interest

There are three research teams working within Aircraft Design Division. They are involved in:

- Aircraft design research
- Aerospace numerical analyses
- Aircraft composite structures investigations

Research laboratories

Aircraft Design Department uses the following research infrastructure:

- commercial computer-aided design tools CAD/CAM (NX Unigraphics)
- commercial numerical tools for the analysis of:
 - o aerodynamic characteristics (potential flow methods, Euler's methods)
 - o aircraft flight mechanics
 - o structures strength (Ansys, Nastran)
 - o mechanism operation
- proprietary software, including:
 - aerodynamic analysis software implementing the low-order panel method (PANUKL)
 - export of numerical model for FEM analysis (integration with Calculix)
 - software tool for mass analysis of an aircraft's structure
 - dynamic stability analysis of an aircraft (stability, simulation, and control) – SDSA
 - o numerical optimisation software
 - software for propellers design
 - integration of in-house tools with the commercial software ANSYS



- strength laboratory
 - o strength test stand for full-size aircraft tests in elevated temperature (up to 60°C)
 - INSTRON strength testing machine with 10 kN and 200 kN load cells, and a set of extensometers
 - o ElectroPlus machine with 3kN load cell for fatigue testing
 - o strain measurement systems, including DIC and strain gauge measurement system
 - o linear position sensors
 - OmniScan MX2 Phased Array
 - o SYLES S-Line-400 interrogator
- mechanical workshop allowing small aircraft assembly
- bonding laboratory allowing small-batch manufacture of composite components
 - 4m x 1m x 8 m oven for curing polymer composites at temperatures up to 200°C,
 - o vacuum pumps
 - o temperature and pressure recorders
 - \circ hot bonder with a set of electric heated blankets, thermocouples, and a vacuum system
 - portable system for composite material removal,
- processing workshop allowing CNC milling and lathing, electro-erosive processing and 3D printing of polymers and metals
 - AVIA X-5 1000/500 five-axis machining centers
 - o 3D printers: (Fortus 450MC, Orleas Creator)
- access to aerodynamics laboratory
- access to Przasnysz airfield with flight test infrastructure

Key research project

- Flying laboratory for electric propulsion testing at various altitudes of flight (NCN, 2022-2025)
- Further development of PW-6 glider (Glider Factory "JEŻÓW, 2022-2023)
- Participation in the design, manufacture, testing, and certification processes of the ORLIK unmanned aerial vehicle (2020–2023)
- Design and development of a mid- and longrange unmanned aerial vehicle dedicated to carry loads or measurement equipment (Smart Growth Operational Programme, Spectre Solutions Sp. z o.o., 2018–2021)



- Design of a new fuselage for an aerobatic glider with an FES drive system (Glider Factory "JEŻÓW", Smart Growth Operational Programme)
- CENTRELINE Demonstration of the proof of concept for a ground-breaking approach to synergistic propulsion-airframe integration, the so-called propulsive fuselage concept, (EU, H2020, 2017 – 2020)

- Fuel cell-based Hybrid Drive of a lightweight aircraft (NCBR, 2015–2019)
- AFLONEXT Proving and maturing highly promising flow control technologies for novel aircraft configurations to achieve a quantum leap in improving aircraft's performance and thus reducing the environmental footprint, (EU, FP7, 2013-2018)
- MONICA A new approach to monitoring climate changes in Antarctic ecosystems development of the PW ZOOM unmanned aerial vehicle and its deployment during an Antarctic expedition to conduct research into the Antarctic ecosystem, (POL-NOR, 2013-2016)
- MOSUPS Dynamically similar model of joined-wing aircraft (NCBR, PBS1, 2013–2016)





- ESPOSA Development and integration of novel design and manufacture technologies for a range of small gas turbine engines up to approx. 1000 kW to provide aircraft manufacturers with better choice of modern propulsion units, (EU, FP7, 2011-2016)
- Development of assumptions, design, and prototype manufacture of a new-generation TSA hybrid aircraft dynamic stability analysis (ATP AVIATION Sp. z o.o., 2013–2015)
- Development of non-adhesive metal-composite lock joint for introducing concentrated loads into primary layered structures made of carbon/epoxy prepregs (NCBR, 2012– 2015)
- Development of an out-of-autoclave manufacturing process for composite aircraft structures made of carbon/epoxy prepregs (NCBR, 2012–2015)
- Tests of a micro UAV with a LEX and in a pusher propeller configuration (NCN, Preludium, 2012–2014)
- Nowa koncepcja sterowania samolotem wysokomanewrowym, (NCN, Preludium, 2011-2013)
- PPLANE systematic approach to radical and novel ideas for Personal Air Transport System, (EU, FP7, 2009-2012)
- New-generation multi-functional two-seater motor glider (Ministry of Science and Higher Education, 2008–2012)
- SimSAC Simulating Aircraft Stability and



Control Characteristics for Use in Conceptual Design, (EU, 6th Framework Programme, 2006–2010)

- Unmanned Airplanes with strake wing (Ministry of Science and Higher Education, 2009– 2012)
- NACRE New aircraft concepts research, (EU, FP6, 2005-2010)
- Lightweight unmanned aerial vehicle (technology demonstrator vehicle) for surveillance in civilian applications – SAMONIT (Ministry of Science and Higher Education, 2007–2009)
- CAPECON aimed to advance the utilisation of safe and low cost Unmanned Air Vehicles (UAVs) in the civilian commercial sphere, (EU, FP5, 2002-2005)



Relevant achievements

- Implementation of the proprietary software developed by team in the teaching process (University of Brighton)
- Application of software modules for conceptual studies (Airbus Poland)
- CENTRELINE Consortium with 9 partners from Germany, France, Sweden, Netherlands, United Kingdom
- AFLONEXT Consortium of 40 partners from 15 countries.
- MONICA Consortium with partner from Norway
- ESPOSA Consortium of 44 partners from 15 countries.
- PPLANE Consortium of 44 partners from 11 countries.
- SimSAC Consortium of 13 partners from 9 countries.
- NACRE Consortium of 36 partners from 10 countries.
- CAPECON Consortium of 19 partners from 8 countries.
- Design of the airframe of the first Polish multifunctional two-seater motor glider with electric propulsion (AOS-71), followed by prototype test flights and placing into service (KB/68/12823/IT1-B/U/08, 2008-2012); further development (AOS-H2) of this design with a fuel cell (PBS3/A6/24/2015, 2015-2018)
- Prime Minister's 1st Degree Team Award for the outstanding scientific and technical achievement: "PW-6 two-seater new-generation training glider";



implementation of the glider into batch production and support for its further development (Smart Growth Operational Programme 2020); more than 60 gliders have been built and sold all over the world

• PW-5 glider's win in the FAI "world-class glider" competition in 1993; implementation of the glider into batch production and production support (more than 300 gliders have been built and sold all over the world)

Selected relevant publications

Books

- Galiński C., Wybrane zagadnienia konstrukcji samolotów, Wydawnictwa Politechniki Warszawskiej, Warszawa 2020, ISBN 978-83-8156-115-0 <u>https://itlims-</u> zsis.meil.pw.edu.pl/pomoce/BIPOL/Galinski Wybrane zagadnienia konstrukcji samolo tow.pdf
- Galiński C., Wybrane zagadnienia projektowania samolotów, Wydawnictwa Instytutu Lotnictwa, Warszawa 2016, ISBN: 978-83-63539-31-3, eISBN: 978-83-63539-36-8, <u>https://ilot.lukasiewicz.gov.pl/Cezary Galinski Wybrane zagadnienia projektowania s</u> <u>amolotow.pdf</u>

Papers

- Goetzendorf-Grabowski T., Flight dynamics of unconventional configurations, Progress in Aerospace Sciences, vol. 137, February 2023, 100885, <u>https://doi.org/10.1016/j.paerosci.2023.100885</u>
- 2. Goraj Z., Kowalski M., et al., Proof of Concept Study for Fuselage Boundary Layer Ingesting Propulsion, Aerospace, Volume 8, Issue 1, No 16, 2021, <u>https://doi.org/10.3390/aerospace8010016</u>
- 3. Rodzewicz M., et al., Mapping Glacier Forelands Based on UAV BVLOS Operation in Antarctica, Volume 12 Issue 4, No 630, 2020, <u>https://doi.org/10.3390/rs12040630</u>
- Galińska A., Galiński C., Mechanical Joining of Fibre Reinforced Polymer Composites to Metals-A Review. Part II: Riveting, Clinching, Non-Adhesive Form-Locked Joints, Pin and Loop Joining, Polymers, Volume 12 Issue 8, No 1681, 2020, <u>https://doi.org/10.3390/polym12081681</u>
- Mieloszyk J., Tarnowski A., Tomaszewski A., Goetzendorf-Grabowski T., Validation of flight dynamic stability optimization constraints with flight tests, <u>Aerospace Science and</u> <u>Technology</u>, <u>Volume 106</u>, November 2020, 106193, <u>https://doi.org/10.1016/j.ast.2020.106193</u>
- Kustroń K., Goraj Z., et al., New hail impact simulation models on composite laminated wing leading edge, Aircraft Engineering and Aerospace Technology, Vol. 91 No. 3, 2019, pp. 457-465. <u>https://doi.org/10.1108/AEAT-02-2018-0089</u>
- Grendysa W., Multidisciplinary wing design of a light long endurance UAV, Aircraft Engineering and Aerospace Technology, Vol. 91 No. 6, 2019, pp. 905-914. <u>https://doi.org/10.1108/AEAT-09-2018-0256</u>
- 8. Rodzewicz M., et al., Application of UAV BVLOS remote sensing data for multi-faceted analysis of Antarctic ecosystem, Remote Sensing of Environment, Volume 217, November 2018, Pages 375-388, <u>https://doi.org/10.1016/j.rse.2018.08.031</u>

- Goraj Z., Kustroń K., Review of current research trends in bird strike and hail impact simulations on wing leading edge, Aircraft Engineering and Aerospace Technology, Vol. 90 No. 4, 2018, pp. 602-612. <u>https://doi.org/10.1108/AEAT-02-2017-0053</u>
- Goetzendorf-Grabowski T., Rodzewicz M., Design of UAV for photogrammetric mission in Antarctic area, Proc. Instn. Mech. Engrs. Part G: J. Aerospace Engineering, Volume 231, Issue 9, 2017, Page 1660-1675, <u>https://doi.org/10.1177/0954410016656</u>
- Goetzendorf-Grabowski T., Mieloszyk J., Common computational model for coupling panel method with finite element method, Aircraft Engineering and Aerospace Technology, Vol. 89 No. 5, 2017, pp. 654-662. <u>https://doi.org/10.1108/AEAT-01-2017-0044</u>
- Mieloszyk J., Goetzendorf-Grabowski T., Introduction of full flight dynamic stability constraints in aircraft multidisciplinary optimization, Aerospace Science and Technology, Volume 68, September 2017, Pages 252-260, <u>https://doi.org/10.1016/j.ast.2017.05.024</u>
- Goetzendorf-Grabowski T., Figat M., Aerodynamic and stability analysis of personal vehicle in tandem-wing configuration, Proc. Instn. Mech. Engrs. Part G: J. Aerospace Engineering, Volume 231, Issue 11, 2017, Page 2146-2162, <u>https://doi.org/10.1177/0954410016662</u>
- Figat M., Kwiek A., Aerodynamic optimisation of the rocket plane in subsonic and supersonic flight conditions, Proc. Instn. Mech. Engrs. Part G: J. Aerospace Engineering, Volume 231, Issue 12, 217, 2017, Page 2266-2281, https://doi.org/10.1177/0954410017723672
- 15. Czarnocki P., Bajurko P, Numerical and experimental investigations of embedded delamination growth caused by compressive loading, Journal of Theoretical and Applied Mechanics, Volume 52, Issue 2, 2014, Page 301-312, <u>https://doi.org/10.15632/jtam-pl/157011</u>
- 16. Goraj, Z., Flight dynamics models used in different national and international projects, Aircraft Engineering and Aerospace Technology, Volume 86 Issue 3, 2014, Page 166-178, <u>https://doi.org/10.1108/AEAT-02-2013-0036</u>
- T. Goetzendorf-Grabowski, D. Mieszalski, E Marcinkiewicz: Stability analysis using SDSA tool, Progress in Aerospace Sciences, Volume 47, Issue 8, November 2011, Pages 636–646, <u>https://doi.org/10.1016/j.paerosci.2011.08.007</u>
- A. Rizzi, P. Eliasson, T. Goetzendorf-Grabowski, J.B. Vos, M. Zhang, T.S. Richardson: Design of a canard configured TransCruiser using CEASIOM, Progress in Aerospace Sciences, Volume 47, Issue 8, November 2011, Pages 695-705, <u>https://doi.org/10.1016/j.paerosci.2011.08.011</u>

Division of Automation and Aeronautical Systems

Institute of Aeronautics and Applied Mechanics Faculty of Power and Aeronautical Engineering Warsaw University of Technology

Research Interests

The Division of Automation and Aeronautical Systems conducts research in various aspects of aeronautics, including control and navigation, rotorcraft, and simulators. The Division is actively involved in a number of scientific and research activities, such as modeling and simulation of the dynamics of various mobile platforms, including aircraft, missiles, land vehicles, sea vessels, and satellites.

The Division also develop advanced control methods and algorithms using analytical mechanics and design automatic flight control systems for mobile platforms. In addition, they create simulators that accurately replicate the experience of flying or operating a variety of vehicles and systems.

Research activities also include the study of navigation methods and systems, as well as complex system-of-systems problems. The team studies the aeromechanics of rotorcraft and analyzes human-machine systems.

Overall, the Division of Automation and Aeronautical Systems is dedicated to advancing the field of aviation through innovative research and development. They're committed to pushing the boundaries of what's possible and shaping the future of flight.

Research Laboratories

The Division of Automation and Aeronautical Systems has an advanced research and laboratory infrastructure, including state-of-the-art technologies and equipment to support ongoing research efforts.

The Simulation Laboratory is equipped with two manned aircraft simulators and several unmanned vehicle training devices. The infrastructure of the manned aircraft simulators consists of aircraft cabins (including the Leonardo PZL SW-4 helicopter, fig. 1), two industrial computer sets with software, instructor operation stations and visualization systems, allowing the simulation of various flight scenarios and the testing of control systems in a safe and controlled environment. As a result of a collaboration with the Boeing Company, a simulator of the Boeing 737 MAX jetliner will soon be built in the Division's simulation laboratory. The simulator will be an advanced training tool to help students learn how to develop simulators. It will be a full-size replica of the aircraft cabin, complete with controls, displays, and panels for onboard systems.



Fig. 1 Leonardo PZL SW-4 simulator



Fig. 2 Unmanned aircraft visualization

In addition, the Division has a series of small unmanned helicopters and airplanes, mobile ground robots, the FLIGHTLAB simulation and design software, specifically designed to model the dynamics of flying objects, especially rotorcraft, and control systems such as flyby-wire systems with autopilots.

The control and navigation laboratories are equipped with the latest technologies and various sensors, such as GPS receivers, inertial navigation sensors, inductive and magnetoresistive magnetic compasses, image processing cameras, air data computer, PLC controllers, and more.

Finally, the division has a Laboratory of Autonomous Moving Objects, which explores the latest advances in autonomous technologies and artificial intelligence.

The Division's research and laboratory infrastructure is designed to support ongoing efforts to advance the field of aeronautics. The division is dedicated to exploring new technologies and pushing the boundaries of what's possible, and looks forward to continuing its research in this dynamic field.

Key Research Project

The Division of Automation and Aeronautical Systems has been involved in a wide range of projects, spanning from international collaborations with the industry to national initiatives. These projects have contributed to cutting-edge research and development in areas such as unmanned systems, flight control systems, and aircraft concepts. Here are some of the

major projects in which the division has participated.

International projects sponsored by the industry:

- OpUSS (Optimization of Unmanned System of Systems), figs. 3 and 4;
- Student projects sponsored by The Boeing Company.



Fig. 3 OpUSS project - project team at The Przasnysz Airfield



Fig. 4 OpUSS project - visit to Lockheed Martin, TX, USA

Projects of the 5/6/7 Framework Program and the H2020 Program of the European Union:

- SEA-AHED (Simulation Environment and Advisory System for On-board Help, and Estimation of Maneuvering Performance During Design);
- ADFCS II (Affordable Digital Fly-By-Wire Flight Control Systems for Small Commercial Aircraft Second Phase);
- NICE-TRIP (Novel Innovative Competitive Effective Tilt Rotor Integrated Project);
- NEFS (New Track Integrated Electrical Single Flap Drive System);
- NACRE (New Aircraft Concepts Research);
- TALOS (Transportable Autonomous patrol for Land bOrder Surveillance system);
- CAPECON (Civil UAV Applications & Economic Efficiency of Potentat Configuration solutions);
- ACROSS (Advanced Cockpit for Reduction of Stress and Workload);
- ONION (Operational Network of Individual Observation Nodes).

Polish national projects:

- An Autonomous System For Detecting and Destroying Non-Metallic Mines;
- PROTEUS (Integrated Mobile System Supporting Anti-Terrorist and Anti-Crisis Actions);
- SATSERWIS (Mutual Satellite Navigation System for In-Orbit Servicing and Formation Flight);
- MYSTERY (Aircraft Control System Synthesis Methodology, Taking Into Account High-Risk Situations);
- BPL (Unmanned Land Platforms);
- APN (Autonomous Surface Vessels);
- Development of Missile Control Systems Technology;
- HELIMARIS (Modification of an Optionally Piloted Helicopter for Maritime Mission Performance).

Relevant Achievements

The Division is currently collaborating with numerous academic and industrial partners in Europe and the USA within the framework of EU Framework Programs, national programs and external contracts. The main partners are: The Boeing Company, Lockheed Martin, Leonardo PZL Świdnik, General Electric, Thales Alenia Space.

Other Information

The Division of Automation and Aeronautical Systems has successfully organized the 45th edition of the European Rotorcraft Forum, a prestigious event that brings together experts from industry, academia, and regulatory agencies. It was held in Poland, at the Warsaw University of Technology for the first time, and the team of the Division played a key role in making it a success (fig. 5).



Fig. 5 Organizers of the 45th European Rotorcraft Forum

The successful organization of the European Rotorcraft Forum demonstrates the Division's commitment to advancing the field of aeronautics, and their ability to bring together key stakeholders to share knowledge and ideas. The division looks forward to continued participation in such events and to further contributing to the advancement of rotorcraft technology.

Selected Relevant Publications

This chapter lists of selected relevant publications from the Division of Automation and Aeronautical Systems. The publications include books and key papers/conference materials from 2011 onwards. The books cover topics related to model-based control of nonlinear systems, dynamics, and control of mechanical systems, and satellite navigation systems. The key papers and conference materials cover a wide range of topics, including mobile robot motion tracking, analysis of vibrations in crane systems, optimal control of helicopters, selection of UAVs for ground target tracking, aircraft status supervision, helicopter autopilot

performance evaluation, automated control of a fleet of various UAS, and helicopter control during landing on a moving confined platform.

List of books:

- 1. Jarzębowska E., "Model Based Control of Nonlinear Systems", Modern Mechanics and Mathematics, 2012
- 2. Jarzębowska E., "Dynamika i sterowanie układami mechanicznymi", Wydawnictwo Naukowe PWN, 2021
- 3. Narkiewicz J., "GPS i inne satelitarne systemy nawigacyjne", Wydawnictwa Komunikacji i Łączności, Warszawa, 2007.
- 4. Narkiewicz J., "Podstawy układów nawigacyjnych", Wydawnictwa Komunikacji i Łączności, Warszawa 1999.

List of key papers and conference presentations:

- Jarzębowska E., "A Velocity Observer Design for Tracking Task-Based Motions of Unicycle Type Mobile Robots", Communications in Nonlinear Science and Numerical Simulation, 2011
- 2. Jarzębowska E. et al., "Analysis of influence of a crane flexible supports, link flexibility and joint friction on vibration associated to programmed motions execution", Journal of Vibration Engineering & Technologies, 2019
- 3. Bibik P., Narkiewicz J., "Helicopter Optimal Control After Power Failure Using Comprehensive Dynamic Model", Journal of Guidance Control and Dynamics, 2012
- 4. Kopyt A., Narkiewicz J., Małecki T., Radziszewski P., "Optimal selection of UAV for ground target tracking", Journal of Aircraft, 2015
- 5. Narkiewicz J., Żugaj M., Kopyt A., Topczewski S., "Aircraft Status Supervision System Concept", Journal of Aerospace Engineering, 2017
- 6. Kopyt A., Topczewski S., Żugaj M., Bibik P., "Automatic System for Helicopter Autopilot Performance Evaluation", Aircraft Engineering and Aerospace Technology, 2019
- 7. Kopyt A., Bibik P., "Increase of flight operations effectiveness using automated control over a fleet of various UAS", European Journal of Remote Sensing, 2019
- 8. Topczewski S., Narkiewicz J., Bibik P., "Helicopter Control During Landing on a Moving Confined Platform", IEEE Access, 2020
- 9. Topczewski S., Żugaj M., Bibik P., "Impact of Actuators Backlash on the Helicopter Control During Landing on the Moving Confined Platform", Aircraft Engineering and Aerospace Technology, 2021
- 10. Żugaj, M., Edawdi, M., Iwański, G., Topczewski, S., Bibik, P., Fabiański, P., "An Unmanned Helicopter Energy Consumption Analysis", Energies, 2023

Division of Fundamentals of Machine Design

Institute of Aeronautics and Applied Mechanics Faculty of Power and Aeronautical Engineering Warsaw University of Technology

Research interest

Experimental research and tribology

- strength and stiffness properties of composites,
- experimental methods in the construction and testing of machinery and equipment,
- field (optical) methods,
- incremental manufacturing of structural elements and buildings (3DCP).

Risk and reliability

- risk estimation in selected human-technical-environment systems,
- modeling and analysis of occupational risks.

Biomechanics

- biomechanics of impact,
- biomechanics of sport,
- FEM modeling.

Research laboratories

Soft tissue research laboratory [15]



Experimental testing (DIC strain measurement)





FE modeling

Yacht laboratory

Remote controlled sailing boat used to analyse the mast stiffness influence on the yacht performance.





Forces, wind and velocity measurement



Sail shape registration

1:5 scaled hull of the OPEN 30 class



3D printers


Topology optimization with FEM

Key research project

Improving accessibility to culture and activating disabled and socially excluded people Research project in the Gospostrateg program. The aim of the project is to activate people with disabilities.



Selected objects of the test stand for the study of tactile reading sensations of spatial objects by blind and visually impaired people

Innovative simulation technologies for evaluating vehicle automation systems in terms of road traffic safety [9, 11]



Mini-simulator stand for testing of Advanced Driving Assistance Systems (ADAS)



Screens from the testing environment

Research of riveted joints in aircraft composite structures[13, 14]





Results – comparison of strain from DIC and FEM

Relevant achievements

Piezo transducer with spiral electrodes

Patent No. 225481

New sensor [18] has good accuracy in the study of deformation. Possibility of application to study low-frequency waveforms, using the new charge amplifier with high impedance input.



Transducer scheme and single fiber prototypes

Developing a line of innovative wakeskate boards

NCBR-funded implementation research project.

Development of an innovative wakeskate board based on tested and classified board parameters, allowing to reach its best and optimal features.



Final product and FEM analysis

3DCP – 3D Concrete Printing

System for manufacturing reinforced 3DCP prints



3D Printer designed for large-scale projects



First buildnig in Poland printed on site

RUF Guitars

Innovative composite instruments made of Ruffaine - the most advanced, fully adjustable material scientifically designed to get the perfect tone.



The product and Ruffaine in mold

Other information

Division of Fundamentals of Machine Design organizes bianualy Symposium on Experimental Mechanics in memory of prof. Jacek Stupnicki

Selected relevant publications

- Abratański, A., Grzejda, R., & Perz, R. (2023). Feasibility study of topology optimization of the control system frame for the missile with canard configuration. *Aircraft Engineering and Aerospace Technology*, 95, 1–7. https://doi.org/10.1108/AEAT-04-2022-0109
- Papis, M., & Krawczyk, T. (2022). Comparison of MIG-29 and F-16 aircraft in the field of susceptibility to destruction in combat. *Aviation*, 26, 131–137. https://doi.org/10.3846/aviation.2022.17592
- Rządkowski, W., Klik, P., Tracz, J., & Kowalik, M. (2022). Case Study of Composite Chassis Manufacturing Process Using Low Temperature Molds Tempered with Gradual Heat Annealing Process. *Advances in Science and Technology Research Journal*, 16, 12–21. https://doi.org/10.12913/22998624/147368
- Stepnowski, M., Janczak, D., Jakubowska, M., & Pyrzanowski, P. (2022). Surface Damage Assessment by Analysis of Electrical Resistance Changes in Graphite-Based Sensing Skin. *Metrology and Measurement Systems*, 29, 1–13. https://doi.org/10.24425/mms.2022.140037
- 5. Bereś, Ł., & Pyrzanowski, P. (2021). The Gantry as a Drive for a Horizontal Bike: Initial Investigation of rotary Work. *Applied Bionics and Biomechanics*, 2021, 1–12. https://doi.org/10.1155/2021/6654377
- Rządkowski, W., Jan, T., Adam, C., Kamil, G., Hubert, G., Palka, M., & Kowalik, M. (2021). Evaluation of Bonding Gap Control Methods for an Epoxy Adhesive Joint of Carbon Fiber Tubes and Aluminum Alloy Inserts. *Materials*, 14, 1–13. https://doi.org/10.3390/ma14081977
- Bielawski, R., Rządkowski, W., Kowalik, M., & Kłonica, M. (2020). Safety of Aircraft Structures in the Context of Composite Element Connection. *International Review of Aerospace Engineering (IREASE)*, 13, 159–164. https://doi.org/10.15866/irease.v13i5.18805
- 8. Lindstedt, Ł., Rodzewicz, M., Rzymkowski, C., & Kędzior, K. (2019). Impact Loads and Crash Safety of the Cockpit of a Composite Glider. *Fatigue of Aircraft Structures*, 2019, 39–55. https://doi.org/10.2478/fas-2019-0005
- Papis, M., Jastrzębski, D., Kopyt, A., Matyjewski, M., & Mirosław, M. (2019). Driver reliability and behavior study based on a car simulator station tests in ACC system scenarios. *Eksploatacja I Niezawodność*, 21, 511–521. https://doi.org/10.17531/ein.2019.3.18.
- Deskiewicz, A., & Perz, R. (2017). Agricultural Aircraft Wing Slat Tolerance for Bird Strike. *Aircraft Engineering and Aerospace Technology*, *4*, 590–598. https://doi.org/10.1108/AEAT-11-2016-0220
- Dziewoński, T., Golon, K., Jastrzębski, D., Kopyt, A., Mirosław, M., Matyjewski, M., & Papis, M. (2017). From aDRIVE Project to INTEGRATED Safety. *IRCOBI Conference Proceedings*, 34–35.

- Woch, M. (2017). Reliability analysis of the PZL-130 Orlik TC-II aircraft structural component under real operating conditions. *Eksploatacja I Niezawodność*, 19, 287– 295. https://doi.org/10.17531/ein.2017.2.17
- Bielawski, R., Kowalik, M., Suprynowicz, K., Rządkowski, W., & Pyrzanowski, P. (2016). Investigation of Riveted Joints of Fiberglass Composite Materials. *Mechanics* of Composite Materials, 52, 199–210. https://doi.org/10.1007/s11029-016-9573-4
- 14. Bielawski, R., Kowalik, M., Suprynowicz, K., & Pyrzanowski, P. (2016). Possibility of usage of aluminium rivet nuts connections in composite materials. *Solid State Phenomena*, 240, 137–142. https://doi.org/10.4028/www.scientific.net/SSP.240.137
- Kowalik, M., Pyrzanowska, J., Piechal, A., Blecharz-Klin, K., Widy-Tyszkiewicz, E., Obszański, M., Suprynowicz, K., & Pyrzanowski, P. (2016). Determination of mechanical properties of rat aorta using ring-shaped specimen. *Solid State Phenomena*, 240, 255–260. https://doi.org/10.4028/www.scientific.net/SSP.240.255
- 16. Mirosław, M., & Jastrzębski, D. (2015). Human Body Behaviour as Response on Autonomous Maneuvers, Based on ATD and Human Model. *Journal of Mechanics Engineering and Automation*, *5*, 497–502.
- Perz, R., Toczyski, J., & Subit, D. (2015). Variation in the human ribs geometrical properties and mechanical response based on X-ray computed tomography images resolution. *Journal of the Mechanical Behavior of Biomedical Materials*, 41, 292–301. https://doi.org/10.1016/j.jmbbm.2014.07.036
- Rządkowski, W., Suprynowicz, K., & Pyrzanowski, P. (2015). Influence of Piezoelectric Transducer To Glass Fiber Reinforced Composite Stiffness. Advances in Science and Technology Research Journal, 9, 106–111. <u>https://doi.org/10.12913/22998624/59091</u>

Division of Theory of Machines and Robots

Institute of Aeronautics and Applied Mechanics Faculty of Power and Aeronautical Engineering Warsaw University of Technology

Research interest

- Multibody systems: dynamics, numerical methods, modeling of friction phenomenoms
- High-performance computing
- Overconstrained mechanical systems
- Artificial intelligence for robotics and in general applications including vision and arificial neural networks
- Control systems: design and synthesis, data-driven identification & control, optimal control
- Motion analysis and design, intelligent navigation
- Robotics: parallel robots, medical robots, humanoids, prostheses, arificial limbs. assistive robotics, novel designs
- Biomechanics: injury, impacts, child restraint systems

Research laboratories

Industrial Robotics Laboratory

Two KUKA LWR4+ robots with KR C2 controllers



Fig. 1 KUKA LWR4+ robots

The KUKA Lightweight 4 robots are kinematically redundant (i.e., seven DOF), have a total weight of less than 15 kG with a range up to 1.5 m. They have have high dynamic performance. Each joint has torque sensors coupled to the harmonic drive, with torque measurement error of less than 0.5%, the low pass filter eliminates the noise. Combination of position and torque sensors allows the implementation of position and impedance control.

KUKA Agilus with KR C4 controller



Fig. 2 KUKA Agilus

The KR AGILUS is our compact six-axis robot that is designed for particularly high working speeds.

Technical data:

- Maximum reach 901.5 mm
- Maximum payload 6 kG
- Pose repeatability (ISO 9283) ± 0.03 mm
- Number of axes 6
- Weight approx. 52 kG
- Cycle time: 150 cycles per minute (path: 25 mm / 305 mm / 25 mm, payload 1 kG)

Fanuc M10iA robot with 2-axis positioner



Fig. 3 Fanuc M-10iA

Fanuc M-10iA is a compact structure comparing to the other robots of its class, while maintaining high speed in its axes with very good repeatability. The M-10iA can carry loads weighing up to 10 kG with a horizontal range of 1420 mm.

Fanuc M1iA parallel manipulator with vision system and vacuum gripper



Fig. 4 Fanuc M-1iA

High-speed 6 axes delta robot has a payload 1 kG and a working range 420 mm. iRVision camera allows to locate the parts and the assising software allows to obtain its precise position and orientation.

Mobile Robotics Laboratory

Research on:

- SLAM,
- machine intelligence and autonomy,
- sensor fusion,
- mobile robot navigation,
- path planning,
- robot cooperation,
- motion synthesis,
- humanoid robots design,

- humanoid robots motion generation,
- human-inspired control techniques,

On-board equipment of mobile robots:

- control computers,
- manipulators with grippers,
- on-arm cameras;
- stereo-vision sensors,
- laser distance scanners,
- wireless communication equippment,
- GPS,
- inertial measurement units,
- sonars,
- bumper sensor











Fig. 5 Mobile Robotics Laboratory equipment

Measurements, Automation and Control Laboratory

Laboratory stands include:

- NI measurement computers (PXI 1078, CompactRIO 9038, myRio 1900) and an assortment of sensors and data acquisition cards,
- high-speed cameras (FASTEC TSCHERMS, PHANTOM 310v) with ancillary equipment
- 3D Smarttech scanner
- PLC test stand (Simatic S7-1200+HMI, Astraada One Compact ECC2100)
- QUANSER research platform
- Maxon EPOS2 testbeds



Fig. 6 Measurement, Automation and Control Laboratory equipment

Vision Systems Laboratory

The laboratory equipment consists of one Basler industrial camera and two LED lights with variable intensity and color temperature (Fig. 7), Jetbot robot with vision system (Fig. 8). The laboratory equipment is used in student research for engineering and master thesis, and laboratory of Digital Image Processing is currently focused on computer vision problems in varying light conditions.



Fig. 7 Two LED lights and a camera — research on the influence of the light condition on object detection (source: Maciej Zieja, *The chess pieces detection system of a robot for chess games in changing lighting conditions*, engineering thesis, 2023)



Fig. 8 Jetbot robot with the periphery equipment (Source: own elaboration)

The laboratoty is used to conduct research in the field of segmentation, detection, and tracking of the objects using visual data. Research concerns also color images acquisition like colorimetric calibration, vignetting correction, or image denoising. A part of the research is application of computer vision in robotics using the Robot Operating System (ROS).

Computational environment

A high performance ASUS ESC4000 G4 server is utilized as a hardware platform for running customised simulation algorithms, mainly from the field of multibody system dynamics. The machine is equipped with two Xeon Gold 6242 CPU, 192GB of DDR4 RAM, and 1 Nvidia Quatro RTX600 GPU. It runs Ubuntu Linux. Development toolchains, including GCC, LLVM, and other tools necessary for development are available at hand or installed on demand. The machine is used in research projects, mainly as a development and test platform for parallel simulation and optimization algorithms.

Key research projects

Hamiltonian approach toward efficient modeling of large-scale multibody systems with friction and toward real-time simulations of robotic systems (NCN OPUS 15, 2018-2022)

In the analysis, design, and optimization of numerous mechanical systems, there is a need for automatic modeling and investigation of complex multibody systems with many bodies and degrees of freedom. In this class of systems, multibody modeling methods are widely used in engineering branches and scientific research. The analyzed mechanical or interdisciplinary objects are becoming increasingly complex. The mentioned systems can be frequently found in such areas as robotics (dynamics of manipulators), automotive (testing of car components and complete vehicles), railroad (e.g., traffic safety), defense (e.g., design of tracked vehicles), aerospace (e.g., analysis of unmanned aerial vehicles or their formations). Multibody models are often used in control systems of many mechanical systems, e.g., in robotics. The developed models allow one to predict the behavior of such systems to achieve the desired response. The natural applications of MBS methods also emerge in space and exploratory robotics.

Multibody modeling techniques play a significant and vital role in applications wherein examining phenomena occurring in the existing system is expensive, time-consuming, or very difficult in technical realization. The analysis and simulation of large-scale multibody systems require significant numerical expenses. Simultaneous enforcement of computational efficiency and high-fidelity physical model requirements is sometimes challenging. However, recent studies suggest that using Hamilton's formalism for the description of multibody system behavior may enhance the performance and significantly increase the efficiency of such computations and, in consequence, may reduce specific barriers associated with real-time applications. In addition, fast calculations with parallel computers, equipped with multicore processors and GPU card arrays, allow one to analyze systems with much greater complexity—with the number of degrees of freedom approaching tens of thousands (biomolecular systems) or even millions of bodies (granular media). The main objective of this project is to develop and investigate highly efficient methods for computer-aided modeling and analysis of complex multibody systems in a unified Hamiltonian approach. The proposed research focuses on three groups of issues in the field of modeling MBS:

- Research objective 1: Developing efficient sequential and parallel algorithms for modeling MBS in the Hamiltonian framework.
- Research objective 2: Research the methods for analyzing complex multi-rigid- or multi-flexible-body systems with friction.
- Research objective 3: Experimental research on complex robotic systems to the extent necessary for verification of the project's theoretical considerations and simulation results.

The results of this project are published in [1], [2], [3], [4].

Efficient indirect optimal control methods for multibody systems (Excellence Initiative, Research University in the field of Artificial Intelligence and Robotics, 2020-2022)

Current problems require engineers to predict how specific parameters or control inputs will affect the behavior of the complex multibody system. In the optimal control or design of MBS, an implicit dependency exists between state and design variables, further adding

complexity to the problem. This branch of computer-aided engineering is tightly combined with **sensitivity analysis**, i.e., efficient computation of the derivatives. To this end, various families of methods have been derived, each having its own set of benefits and drawbacks. The **adjoint method** is one of the more interesting methods for systematically calculating the gradient. The concept behind this approach lies in invoking necessary conditions for the minimum of the optimized functional. Once obtained via variational calculus, these conditions constitute the system adjoint to the dynamic equations of motion – an underlying model of the MBS. Solving the adjoint system yields so-called **adjoint variables**, allowing for efficient gradient computation. The adjoint method can be applied to such problems as optimal control, optimal design, or parameter identification.

Furthermore, the indirect optimal control methodology provides offline (potentially online) trajectory generation tools that can be utilized as a feedforward signal in the control loop. A recent research project involved a practical implementation of the adjoint method in a feedback-feedforward control architecture shown in Fig. 9. A mathematical model has been derived, composed of an electromechanical device with a five-bar multibody system and two DC motors with a gear transmission (Fig. 10). Based on the derived outcome, the input control signal and corresponding trajectory predicted by the model were synthesized. Subsequently, these signals are introduced as reference values to the hardware and compared with classical control algorithms.

The block diagram in Fig. 9 presents a model-based control architecture. Symbol **r** denotes a reference signal that nominally must be enforced. Accordingly, this signal plays the role of an input to the adjoint-based optimization procedure founded on the mathematical model of the MBS. The optimization algorithm yields a control signal $\mathbf{u}_{\rm ff}$ (theoretically) capable of carrying out the required maneuver. The response generated by the model for $\mathbf{u}_{\rm ff}$ is depicted as $\mathbf{y}_{\rm d}$, becoming the actual reference trajectory for the system. Due to the discrepancy between the model and the plant, and the presence of disturbances **d** and measurement noise **n**, it is required to introduce a feedback loop that generates minor corrections $\mathbf{u}_{\rm fb}$ during the execution on the hardware.



Fig. 9 A feedback-feedforward control architecture



Fig. 10 Two-degree-of-freedom closed-loop robotic system

The results of this project are published in [5], [6].

Physics-Based and Data-Driven Multibody System Models For Prediction and Feedforward Robot Control (submitted as a project to NCN OPUS)

As suggested, the control performance stemming from feedback–feedforward control architecture heavily depends on the quality of MBS models, which predict how control inputs affect the system dynamics. First–principles (e.g., Newton–Euler formalism) and identification techniques can be used to derive multibody or robotic system models. Meanwhile, considerable progress has been achieved using machine learning–based approaches that extract complex dynamical behaviors directly from raw experimental or simulation data.

Moreover, for many robotics systems, the dynamics model derived from first-principles or solely based on data may not be sufficiently accurate, especially in the case of unmodelled nonlinearities (e.g., friction, flexibility). This imprecise model leads to a bad prediction of feedforward control, resulting in significant tracking errors, poor control performances, or even damage to the system. Neither a pure physics-based nor a pure **data-driven** approach can be considered sufficient for multibody/robotic tasks with high-dimensional state spaces and complex interactions.

These observations imply the recent group's interest in advancing understanding of the extent to which data-driven paradigms may be combined with pure physics-based models to simulate MBS and generate optimal trajectories. The available state-of-the-art suggests a knowledge gap in this field. Using its previous experience, the group is pushing its area of expertise to (i) integrate MBS formulations with data-driven techniques, (ii) develop a **hybrid modeling** approach for optimal trajectory generation based on the adjoint method, (iii) assess possibilities of practical applications of the developed hybrid models.

Optimal trajectory planning for redundant manipulators

A kinematically redundant structure increases the dexterity of the robotic manipulator and offers an ability to avoid obstacles and handle singularities. Therefore, redundant robots are well-suited for work in human-centered, cluttered environments. However, planning of the joint trajectory that satisfies the desired end effector trajectory and does not exceed the capabilities of the robot joints is not a trivial task.

The Predictive Quadratic Programming Inverse Kinematics with Scaling (PQPIK-S) designed in this project solves this quandary by combining the inverse kinematics (IK) problem with trajectory scaling and solving them simultaneously. The core of the PQPIK-S is the quadratic programming (QP) problem:

$$min_{\dot{\boldsymbol{q}},\lambda}\frac{1}{2}\gamma_0(1-\dot{\lambda})^2 + \frac{1}{2}(\dot{\boldsymbol{q}}-\dot{\boldsymbol{\varphi}})^T \boldsymbol{W}(\dot{\boldsymbol{q}}-\dot{\boldsymbol{\varphi}})$$

w.r.t. $J\dot{q} = v\dot{\lambda}$, $\dot{q}_{min} \leq \dot{q} \leq \dot{q}_{max}$, $0 \leq \dot{\lambda} \leq 1$. The vector $\dot{\phi}$ defines an additional task for a redundant robot (such as obstacle avoidance), whereas parameters γ_0 and W are used to assign weights to different tasks. The end effector velocity $v = v\dot{\lambda}$ is parameterized in terms of virtual time λ , allowing to slow down

the desired motion if (and only if) the joint constraints cannot be satisfied in any other way.

Moreover, the QP problem is formulated in such a way that it utilizes the prediction of the future joint states of the manipulator, allowing to begin the trajectory scaling early, if needed. Outside the prediction horizon, the desired end effector trajectory does not to be

known, allowing for replanning when working in dynamic environments. The obtained joint trajectory is optimal: inside the prediction horizon, it satisfies the end effector trajectory (the main task), fulfills in the best way the secondary tasks (such as joint velocity minimization or obstacle avoidance), and maintains the least possible scaling, all with regards to the joint constraints.



Fig. 11 a) PQPIK-S flow-chart, b) KUKA LWR local frames

The PQPIK-S plays the role of the *joint trajectory planner* block shown in the diagram. It was implemented in C++ with the use of the *Eigen* library for linear algebra and *qpOASES* containing the active-set solver for the QP problem.

Comprehensive simulation studies performed during this project prove the PQPIK-S's advantages compared to the classic IK methods. The most important feature of the PQPIK-S is the ability to satisfy the joint constraints, slowing down the end effector motion only when needed. Moreover, the PQPIK-S computations are done within a 10-millisecond cycle, allowing for a real-time operation. The experiments performed on KUKA LWR 4+ redundant robot present in the Division's Robotics Laboratory prove the feasibility of the PQPIK-S-generated joint trajectories. The experiments were performed with the use of the *Fast Research Interface* – KUKA's interface for the communication between the user's PC and KUKA Robot Controller (KRC).



Fig. 12 Overview of control system arrangement

The results of this project are published in the doctoral dissertation: Woliński Ł., *Optimal trajectory planning for redundant manipulators working in a dynamic environment*, 2021 and in [7].

Formulation and Experimental Validation of Computationally Efficient Methods for Modeling of Hybrid – Rigid-Flexible Multibody Systems with Redundant Constraints–the OPUS-23 grant of National Science Centre of Poland in years 2023-2026 (no. 2022/45/B/ST8/00661)

This project is a continuation of earlier research described in [8], [9], [10], [11], [12], [13]

Multibody systems, i.e., mechanical systems having lots of bodies and degrees of freedom, are commonly used in many areas of modern engineering. Multibody simulation models can be found in diverse areas such as robotics (dynamics of manipulators), automotive (testing of car components and complete vehicles), railroad (e.g., traffic safety), defense (e.g., design of tracked vehicles), etc. Multibody models are also used in control systems.

A simulation model is always a compromise between several objectives; most often, a balance between the accuracy or fidelity of the model and its computational efficiency must be found. This compromise considers many factors, e.g., the availability of the data, the workload needed to build a model, computing capabilities, or the modeling goals. The analysis and simulation of large-scale multibody systems require significant numerical expenses. Simultaneous enforcement of computational efficiency and high-fidelity physical model requirements is difficult to obtain.

The rigid body assumption is frequently adopted in MBS modeling to obtain highly efficient methods. It significantly simplifies the system's physics; nevertheless, multi-rigid-body models can capture essential features of the investigated systems with satisfactory accuracy. There is, however, a broad class of mechanical systems for which the models that assume the rigidity of all the bodies provide erroneous solutions. These systems have redundant constraints (the same degrees of freedom are restrained several times). The redundancy results in the non-uniqueness of calculated joint reaction forces, which may also lead to the non-uniqueness of the simulated motion, making the model useless.

The main aim of the project is to develop general-purpose hybrid (rigid-flexible) modeling methods that will enable reliable simulation of redundantly constrained systems while maintaining high computing efficiency.

The project will be focused on removing or reducing limitations that diminish the scope of applications of the current methods in the context of the system structure, accuracy, efficiency, and fidelity. The research concentrates on the three groups of issues (that are illustrated in Fig. 13).

- Development and investigation of efficient hybrid methods for modeling redundantly constrained MBSs that ensure obtaining physically meaningful solutions. Within this objective, it is planned to propose methods dedicated to the conscious use of both rigid bodies and simplified accounting for compliance of parts in terms of equivalent stiffness or—in another variant—in the form of physics-based penalty factors (in the augmented Lagrangian formulation and similar methods). It should guarantee realistic solutions.
- Development of benchmark problems suitable for testing overconstrained MBSs and examining the numerical properties of formulated modeling methods. One of them should be closely related to the planned experimental setup so that measurements could verify the numerical calculations. The extensive numerical tests will result in both qualitative and quantitative comparison and assessment of various variants of the developed methods.
- Experimental validation of the methods and verification of the simulation results. Within

this research objective, it is planned to design and fabricate an experimental setup to conduct research on MBSs with redundant constraints. The test rig should allow for the adjustment of the assembly stresses. Measurements of both static and dynamic loads ought to be available. Using an industrial robot for introducing external loads or kinematic drive is considered to ensure the repeatability of tests carried out.



Fig. 13 Illustration of the objectives

The following effects of the research are expected:

- developing new numerical tools ready to be implemented in multibody simulation software to conduct automated analyses,
- providing experimental data to validate numerical tools and to get insight into redundancy problems,
- establishing validated benchmark problems for testing MBS models,
- contributing to the state-of-the-art by delivering high-quality papers,
- promoting research in the field of multibody systems with an emphasis on modeling dynamics of overconstrained systems,
- contributing to the growth of the scientific qualifications of the research team members,
- alleviating existing limitations by providing tools for finding a solution to redundancyrelated problems, making it possible to estimate—with acceptable precision—load distribution within an overconstrained multibody system of arbitrary size and topology while maintaining high efficiency.

Tools and methods for novel robotics systems

The research concerns the design and implementation of real-time control systems, focusing on humanoids, walking machines and autonomous flying devices [14]. Motion synthesis methods [15] and design solutions for novel robotic systems inspired by biology are also investigated (Fig. 14 a, b, c, d).

The study of animal movement synergies is needed to translate them into robotic movement patterns. In our earlier research, a motion pattern generator inspired by the biological central pattern generator (CPG) had been developed). By selecting appropriate parameters, the generator captured the synergy of movement in the human hip and knee joints. The generator has been successfully implemented in the bipedal robot – Fig. 14 c.



Fig. 14 Research inspired by biological patterns: (a) small bipedal robot, (b-c) leg with a compliant element, (d) images of the robot gait with compliant feet, (e) images of the gait generated by the Central Pattern Generator (left to right, top to bottom)

A motion similarity measure that allows for an easy and graphical comparison of the displacements of point masses as a function of time has been proposed [16].

Another research stream concerns the EMG based control. In the work [17] fuzzy logic neural network was used to deliver the mapping between the EMG signals and the planned angular position of the upper limb. The simplified dynamic model was used next to produce the based on the difference between the actual joint positions and planned joint positions.

Having in mind the needs of contemporary service robotics the research focuses on predicting human movements and actions using AI methods (Fig. 15). In 'learning by observation' the robot learns what sequence of its body postures is needed to perform a given action and then retrieves from its database the motion primitives (position specifications) to perform the observed sequence of postures. That is, in implementation, the action is defined as a transformation between postures (or primitives). The methods for posture classification using the data recorded by RGB-D cameras have been developed. The method enables the recognition of the activity represented by a sequence of human postures.

The concept of inferring actions based on recognizing elementary motion components using a semantic database or a decision tree also has been studied [18], [19].



Fig. 15 Dynamic prediction of the trajectory of the hand movement (from left to right)

The research concerns aslo the application of modern AI methods in industial robotics for recognition of the machinning defects [20].

Design of a fast two-legged robot with an electric drive using SEA

The project of an electrically driven bipedal robot with SEA (Serial-Elastic-Actuators) with elastic spring elements in the structure is being developed in cooperation with the Kaiserslautern University of Technology. The aim of the work is an attempt to recreate (built-in) in the technical system selected dynamic characteristics important for the walking / running process in order to further study the walking and running of a robot imitating human walking / running to use this knowledge in the construction of humanoid robots.



Fig. 16 Biped robot concept: a) CAD model of the robot, b) a prototype of a limb with 1 DOF made of carbon composite with an SEA actuator drive on a test stand

Design of an elbow joint prosthesis with an electric drive

New materials and technologies have been used to design the electrically powered elbow prosthesis. The main elements of the prosthesis are made of a composite material with the addition of Carbon Fiber Particles by 3D printing. 3D scans of the patient's arm were used to produce the arm support. The method allows for a precise adjustment of the prosthesis to the user's needs. The prosthesis is light, with drives selected to have the appropriate lifting capacity. After being equipped with a hand controlled by myopotentials, the patient will be able to manipulate everyday objects.



Fig. 17 Elbow joint prosthesis with an electric drive: a) CAD model, b) composite material 3D printed prototype of the prosthesis

Analysis of the possibility of reducing children's injuries during road accidents

Children transported by passenger cars require safety systems specially adapted to their needs due to anatomy, physiology and behavior different from adults. The proposed solution to reduce the risk of serious injuries is the use of safety belts integrated with the child restraint system with pretensioners, load limiters and the airbag. The purposes of the research:

- • to identify real life positions in which children travel (experimental research),
- • to assess the risk associated with these positions (numerical research),
- to limit overloads acting on the child's body,
- • to estimate the effectiveness of the proposed safety systems,
- • to investigate statistically significant factors (statistical research),
- • to optimize safety systems for children in order to find the best possible solutions.



Fig. 18 Scheme of research work: the acceleration pulse obtained from the laboratory test and selected numerical models of the sled test and the frontal crash test (50 km/h, 27g, ECE R129)

The research was conducted under permission of the Ethics and Bioethics Committee. The precrash positions were identified in experimental research. The kinematic and injury criteria of the most important regions of the child's body were crucial during optimizing child safety systems (about 20 % risk of an AIS3+ injury).

2187 numerical simulations were performed in one of the statistical plan. Seatbelt parameters had the greatest overall effect on injury responses. The slack in the CRS harness caused a significant increase of injury criteria values. Using airbag resulted in a decrease in normalized values of all injury indicators by approximately 40 %. As a result of the multi-criteria optimization, many solutions near optimal one called Pareto optimal solution were obtained. The scope of the obtained results is even over 90 % for the HIC36 indicator and about 70 % for the HCUM3 indicator (whereas in homologation tests we obtain only one value).



Fig. 19 The intelligent safety belts integrated with the child restraint system with pretensioners, load limiters and the airbag (left) and Pareto optimal solution (right)

It was found that the use of properly adjusted to the individual needs of the child, child restraint system with pretensioners and load limiters reduces the likelihood of serious injuries and death as a result of the frontal collision more than 50 %. The future safety systems (e.g. used in autonomous cars) should cover most of the acceptable positions that a child can take in a properly used restraint system within the scope of road traffic regulations. This research and formulated recommendations may lead to increasing the effectiveness of future safety systems for children, improving methods of their testing and reducing the number of road traffic victims among the population of children in Poland. The team is working on the preparation of a series of patent applications to ensure:

- the child occupant safety by effective dissipation of collision energy,
- the improvement of the ergonomics of child restraint systems,
- the reduction of the risk of death, the minimization of the severity of injuries and long-term effects to the smallest possible level.

Relevant achievements

- Device for spine correction and measurement system: Wojciech Kaczmarek, Krzysztof Mianowski, Marcin Stańczuk, Grzegorz Kamiński, Rafał Rosołek – US Patent No US 9949884.
- Device for spine correction and measurement system (Urządzenie do korekcji kręgosłupa i system pomiarowy): Wojciech Kaczmarek, Krzysztof Mianowski, Marcin Stańczuk, Grzegorz Kamiński, Rafał Rosołek – Polish patent no: PL 229766.
- Device for children transpotation in vehicles (Urządzenie do przewozu dzieci w pojazdach): Michał Kowalik, Edyta Rola, Witold Rządkowski, Karol Suprynowicz – Polish patent no: PL 236856.

Other information

The Division is involved in the acivities of HERITAGE network (https://www.ecnantes.fr/international/our-international-networks/heritage-network) which aims to strengthen higher education cooperation (research and training) between Europe and India in the field of Engineering Sciences: exchange of expertise, organization of scientific workshops, joint participation in international projects, implementation of joint training programme and development of joint research projects as well as scientific diplomacy. The JEMARO – Japan-Europe Master of Advanced Robotics (<u>https://jemaro.ec-nantes.fr/</u>) is locally supervised and realized with the involvement of the Division staff. The Division supports the development of robotics resources in India within the framework of the project IRAS-HUB -101083029 (Capacity Building in Robotics & Autonomous Systems in India). The aim of this Erasmus+ Programme Capacity Building project (2023-2025) is to set up three hubs devoted to Robotics and Autonomous Systems (RAS) in India. The Division is involved in staff training and advising laboratory organization with helping to develop the courses in robotics at the undergraduate and postgraduate level.

Selected relevant publications

- [1] Maciąg P., Malczyk P., Frączek J.: Hamiltonian direct differentiation and adjoint approaches for multibody system sensitivity analysis, International Journal for Numerical Methods in Engineering, vol. 121, 2020, DOI: 10.1002/nme.6512, 200 pkt., IF(3.021).
- [2] Turno Sz., Malczyk P.: FPGA acceleration of planar multibody dynamics simulations in the Hamiltonian–based divide–and–conquer framework, Multibody System Dynamics, 2022, DOI: 10.1007/s11044-022-09860-x, 140 pkt., IF(3.333).
- [3] Malczyk P., Frączek J., González F., Cuadrado J.: Index-3 divide-and-conquer algorithm for efficient multibody system dynamics simulations: theory and parallel implementation, Nonlinear Dynamics, vol. 95(1), 2019, DOI: 10.1007/s11071-018-4593-3, 140 pkt., IF(5.741).
- [4] Marques F., Woliński Ł., Wojtyra M., Flores P., Lankarani H. M.: An investigation of a novel LuGre-based friction force model, Mechanism and Machine Theory, Pergamon Press, 16 vol. 166, 2021, DOI: 10.1016/j.mechmachtheory.2021.104493, 200 pkt., IF(3,866).
- [5] Pikuliński M., Malczyk P.: Adjoint method for optimal control of multibody systems in the Hamiltonian setting, Mechanism and Machine Theory, 104473, vol. 166, 2021, DOI: 10.1016/j.mechmachtheory.2021.104473, 200 pkt., IF(4.93).
- [6] Maciąg P., Malczyk P., Frączek J.: Joint–coordinate adjoint method for optimal control of multibody systems, Multibody System Dynamics, 2022, DOI: 10.1007/s11044-022-09851-y, 140 pkt., IF(3.333).
- [7] Woliński Ł., Wojtyra M.: A Novel QP-Based Kinematic Redundancy Resolution Method With Joint Constraints Satisfaction, IEEE Access, 41023-41037, vol. 10, 2022, DOI: 10.1109/ACCESS.2022.3167403, 100 pkt., IF(3,367).
- [8] Wojtyra M., Pękal M., Frączek J.: Utilization of the Moore-Penrose inverse in the modeling of overconstrained mechanisms with frictionless and frictional joints, Mechanism and Machine Theory, Pergamon Press, 1-19, vol. 153, 2020, DOI:10.1016/j.mechmachtheory.2020.103999, 200 pkt., IF(3,866).
- [9] Pękal M., Wojtyra M., Frączek J.: Free-body-diagram method for the uniqueness analysis of reactions and driving forces in redundantly constrained multibody systems with nonholonomic constraints, Mechanism and Machine Theory, Pergamon Press, 329-346, vol. 133, 2019, DOI: 10.1016/j.mechmachtheory.2018.11.021, 200 pkt., IF(3,312).
- [10] Wojtyra M.: Modeling of Static Friction in Closed-Loop Kinematic Chains—Uniqueness and Parametric Sensitivity Problems. Multibody System Dynamics 39: 337–361, 2017, DOI: 10.1007/s11044-016-9535-6, IF(3.333).

- [11] Wojtyra M., Frączek J.: Solvability of Reactions in Rigid Multibody Systems with Redundant Nonholonomic Constraints, Multibody System Dynamics 30: 153–171, 2013, DOI: 10.1007/s11044-013-9352-0, IF(3.333).
- [12] Wojtyra M.: On Some Problems with Modeling of Coulomb Friction in Self-Locking Mechanisms, Journal of Computational and Nonlinear Dynamics 11: 110081–110090, 2016, DOI: 10.1115/1.4030386, IF(1.872).
- [13] Wojtyra M., Frączek J.: Comparison of Selected Methods of Handling Redundant Constraints in Multibody Systems Simulations, Journal of Computational and Nonlinear Dynamics 8: 1–9, 2013, DOI: 10.1115/1.4006958, IF(1.872).
- [14] Szumowski M., Żurawska M., Zielińska T.: Preview Control applied for humanoid robot motion generation, Archives of Control Sciences, 111-132, vol. 29, 2019, DOI: 10.24425/acs.2019.127526, 100 pkt., IF(1,443).
- [15] Zielińska T., Coba Gabriel R., Ge W.: Variable Inverted Pendulum Applied to Humanoid Motion Design, Robotica, 1-22, 2021, DOI: 10.1017/s0263574720001228, 70 pkt., IF(2.406).
- [16] Zielińska T., Coba G.: The Measure of Motion Similarity for Robotics Application, Sensors, 1-21, vol. 23, 2023, DOI: 10.3390/s23031643, 100 pkt., IF(3.847).
- [17] Lento B., Aoustin Y., Zielińska T.: Feasibility Study of Upper Limb Control Method Based on EMG-Angle Relation, ASME J. Comput. Nonlinear Dynam. 1-5, Paper No: CND-22-1152, DOI: 10.1115/1.4056918 2023, 70 pkt., IF(1.872).
- [18] Dutta V., Zielińska T.: Predicting Human Actions Taking into Account Object Affordances. Journal of Intelligent & Robotic Systems, 745-761, vol. 93, 2019, DOI: 10.1007/s10846-018-0815-7, 100 pkt., IF(3.129).
- [19] Dutta V., Zielińska T.: Prognosing Human Activity Using Actions Forecast and Structured Database. IEEE Access, 1-19, 2020, DOI: 10.1109/ACCESS.2020.2963933, 100 pkt., IF(3,367).
- [20] Wang X., Zhang Y., Liu J., Zhiwei L., Zielińska T., et all.: Online Detection of Weld Surface Defects Based on Improved Incremental Learning Approach, Expert Systems with Applications, 116407, vol. 195, 2022, DOI: 10.1016/j.eswa.2021.116407, 140 pkt., IF(8,665).
- [21] Pawełczyk M., Wojtyra M.: Real World Object Detection Dataset for Quadcopter Unmanned Aerial Vehicle Detection, IEEE Access 8: 174394–174409, 2020, DOI: 10.1109/ACCESS.2020.3026192, 100 pkt., IF(3,367).
- [22] Vonwirth P., Nejadfard A., Mianowski K., et all.: SLIP-Based Concept of Combined Limb and Body Control of Force-Driven Robots, Advances in Service and Industrial Robotics: results of RAAD / Zeghloul Saïd, Laribi Med Amine, Sandoval Arevalo Juan Sebastian (Ed.), Mechanisms and Machine Science, Springer, 547-556, vol. 84, 2020, DOI: 10.1007/978-3-030-48989-2_58.
- [23] Kordecki A.: Fast document area detection for scanned images, The 11th International Conference on Machine Vision (ICMV), Munich, 2019 (indexed in Web of Science), DOI: 10.1117/12.2522926.

Division of Strength of Materials and Structures

Institute of Aeronautics and Applied Mechanics

Faculty of Power and Aeronautical Engineering

Warsaw University of Technology

Research Interest

- Biomechanics:
 - Implants and bone remodeling (hip implants, spinal disc implants, dental implants)
 - Inner ear biomechanics
- Power engineering:
 - Problems of strength of rotating turbomachinery
 - Finite element modeling of material fatigue and cracking problems for steam power system HP devices exposed to thermal shocks
 - o FE analysis of the turbine blade locking piece defects
 - Structures of DEMO fusion reactor (2014-2022)
- Composites, cellular solids, smart and intelligent materials:
 - The prediction of optimal material layout for elastic continum structure using weighted resource constraint
 - Mechanical properties of low-density open & closed cell foams based on tetradecahedronal model of microstructure
 - Nanocomposites: parametric FE modeling of mechanical, electrical and thermal properties of nanocomposite
 - Mechanical joining of composite materials: drilling of glass fiber-reinforced composites
- Mechanics of solids:
 - FE modeling of microscale structures with non-uniform material distribution crystallites (non-linear material properties, large deformation and strain)
 - Sequence of damage events (delamination) occurring in the course of the low energy impact of carbon fiber composites
- Aviation:
 - Explosion resistance of the fuselage
 - Gyrocopter dynamics: prs, rotor braking, L/G

Research laboratory

Laboratory of the Division of Strength of Materials and Structures

The Research Laboratory deals with testing materials, structural elements, and large structures. The laboratory uses works carried out to implement research projects and investments from other scientific research and industry. Modernization of the laboratory was finished in 2022, along with retrofitting with modern equipment, including X-ray tomograph, flaw detectors - ultrasonic (phase Array) and Eddy current, a system for optical deformation measurements (DIC) as well as CNC components and 3D printers for metal.

The laboratory provides its services mainly to companies from the aerospace and automotive industries. Among the current customers of the replacement laboratory are the State Aircraft Accident Investigation Principle, the Air Force Institute of Technology, and several companies from the small business sector.



Infrastructure



Modern equipment



Laboratory tests



Crack at the propeller hub



Testing hyperelastic materials

Key research projects

Bone Conduction Stimulation of the Temporal Bone with the Inner Ear

PBS3/B7/25/2015: "Development of an innovative method of direct stimulation of the inner ear by bone conduction" performed by the consortium WUM-PW-Aurismed S.A.- Signovia International sp. z o.o., 2015-2019.



The subject of numerical analysis was a three-dimensional model of the temporal bone, published in [2] and shown in the figure. The finite element model has well-reconstructed structures of cortical and trabecular parts and included the cochlea, semicircular canals, annular ligament, round window membrane, basilar membrane, spiral lamina, spiral ligament, perilymph fluid, helicotrema, and a titanium cylinder representing the bone

conduction implant, which was attached to the otic capsule bony surface above the lateral semicircular canal. Other parts of the inner ear, such as the balance receptors, Reissner's membrane, tectorial membrane, organ of Corti, and the cochlear duct, were not included. Hence, the passive linear behavior of BM was assumed. The middle and outer ear structures, such as the tympanic membrane, malleus, incus, and the middle-ear ligaments and muscles, were not included, except the stapes. Consequently, only two of the five possible BC sound pathways were considered: the inertia of the perilymph fluid and compression of the cochlear walls. The inertia of the middle-ear ossicles was partially considered in the model with a movable stapes. In contrast, the otosclerotic condition on the annular ligament existed in the model with an immobilized stapes, where the ligament was replaced with a cortical bone. The RW membrane and cortical bone were assumed as viscoelastic, with the storage and loss moduli defined as functions of frequency. Other solid tissues were modeled as linear isotropic. Some properties of the BM and SL were defined as functions of the spatial coordinates and frequency. The cochlear fluid was assumed as viscous and compressible. The dynamic viscosity of the fluid was considered only for vibration damping The cochlea in the model was validated based on the experimental data.



FE modeling of bone conduction in the human ear displacements in the bone, selection of the excitation force

The subject of the work was to develop a method of direct stimulation of the inner ear fixed in place of the otic capsule to improve hearing with minimal stimulator energy and to find design assumptions for a new type of implant utilizing the bone conduction pathway.

Harmonic analysis of the FEM model was a tool to determine displacements of the temporal bone caused by the implant vibrations.

The effectiveness of bone conduction stimulation depended on the force amplitude as a function of frequency, which caused a similar response in the cochlea of the inner ear as for the displacement applied on the stapes. For the optimal direction of stimulation, the forces were the smallest in the analyzed frequency range (0.4 to 10 kHz).

Design and stress analysis of high presser components

Power engineering is one of the most important field for division of strength of materials and structures. Team supported and worked on several project in that area focusing on high pressure components as piping, valves, vessels, reactors, heat exchangers and boilers. The team worked on projects aimed at improving existing structure or emergency support for quick repair of components to ensure the maintenance of installation including gasket tightness issues. Team has experience in both modeling and concept of new design solution. Furthermore team is able to support project in area of reverse engineering finding the root cause of failure.



Steam leakage problem of HP power turbine casing (860MWatts at Lagisza Power Plant)



Quench heat exchanger (model include nonlinear gasket – tightness improvements)

Design of DEMO fusion reactor structure (2014-2022)

As part of the EUROfusion program (as part of the work in the Joint European Program of the EURATOM Community), calculation (design and research) work was carried (2014-2022) aimed at determining the concept of the structure and fastening of the vacuum tank (cryostat) of the DEMO reactor and its biological shield. The DEMO reactor (DEMOnstration Power Station) is an experimental tokamak nuclear fusion reactor in the conceptual phase, designed on the model of the smaller ITER reactor under construction in Cadarache (France).



Contamination protection structure

Strength of turbomachinery components

Team had a chance to work on several R&D projects in filed on turbomachinery. It allowed team to gain experience in both stator and rotor side including creep, fatigue and cracking problems. Several analysis of dynamic behavior of rotos has been performed and verified by tests. As part of the interests, knowledge in the field of bearings is also developed. In addition to the rotors, the team also worked on components such as nozzles and shrouds.



Mechanical joining of composite materials: Drilling of glass fiber reinforced composites

As drilling holes is necessary for bolted joining of composite materials, quality of the holes is one of key factors influencing strength of the joints. Therefore, a research has been made to select the drill material which assures the best hole quality in glass fiber-reinforced composite. Six drills made of different materials have been chosen: plain high speed steel (HSS) (drill 1), HSS with 5% addition of cobalt (drill 2), HSS with 5% addition of cobalt with titanium coating (drill 3), HSS with titanium coating (drill 4), cemented carbide (drill 5) and HSS tipped with tungsten carbide (drill 6). The quality of the holes has been assessed and bearing strength of holes made with use of each drill has been measured. The best results have been achieved for HSS drill with titanium coating. The research was funded by Internal Faculty Grant No. MEiL-847/2019 in Warsaw University of Technology, Faculty of Power and Aeronautical Engineering.



Delamination caused by drill 1

Comparison of FEM (left side of each picture) and DIC (right side of each picture) open hole



Instruments for space missions of the European Space Agency (ESA)

Mechanical objects of very high complexity were analyzed to meet the requirements of space standards (ECSS). The procedure involved many analysis types: thermomechanical, self-vibration, frequency response, random loads, shock loads, and bolt connection analysis.



Selected relevant publications

- 1. Bachmann C. et al.: Containment structures and port configurations. *Fusion Engineering and Design*, 174, 112966, 2022. DOI: <u>10.1016/j.fusengdes.2021.112966</u>.
- Borkowski P. et al.: Bone conduction stimulation of the otic capsule: a finite element model of the temporal bone. *Acta of Bioengineering and Biomechanics*, 21(3), 75-86, 2019. DOI: <u>10.5277/ABB-01401-2019-02</u>.
- Borkowski P., Dacko A., Rodzewicz M.: Synthesis and structural analysis of high strength composite flexible landing gear legs. *Proceedings of the 13th International Scientific Conference* Rusiński E., Pietrusiak D. (eds.), Lecture Notes in Mechanical Engineering, 49-61, Springer, 2017. DOI: <u>10.1007/978-3-319-50938-9 6</u>.
- 4. Ciupiński Ł., Zagrajek T., Marek P. et al.: Design and verification of a non-selfsupported cryostat for the DEMO tokamak. *Fusion Engineering and Design*, 161, 111964, 2020. DOI: <u>10.1016/j.fusengdes.2020.111964</u>.
- 5. Dacko A., Borkowski P., Lindstedt Ł.: Structural dynamics of a gyrocopter: numerical approach in some emergency cases. *Aircraft Engineering and Aerospace Technology*, 90(4), 699-710, 2018. DOI: <u>10.1108/AEAT-11-2016-0217</u>.
- Galińska A.: Mechanical joining of fibre reinforced polymer composites to metals—a review. Part I: bolted joining. *Polymers*, 12, 102252, 2020. DOI: <u>10.3390/polym12102252</u>.
- Galińska A., Galiński C.: mechanical joining of fibre reinforced polymer composites to metals—a review. Part II: riveting, clinching, non-adhesive form-locked joints, pin and loop joining. *Polymers*, 12, 8, 2020. DOI: <u>10.3390/polym12081681</u>.
- Galińska A.: Compensation of process-induced deformations of double-curved carbon–epoxy composite elements. *Polymer Composites*, 40, 9, 3666-3677, 2019. DOI: <u>10.1002/pc.25229</u>.
- 9. Gojny K., Dacko A.: Investigation of finite element (Fe) modelling of composite materials: shell, solid and solid layered composite modelling comparison of impact on simulation results. *Composites, Theory and Practice*, 21(1-2), 29-39, 2021.
- 10. Kamieniecki K., Piechna J., Borkowski P.: Basilar membrane vibration in time domain predicted by fluid–structure interaction model in pre- and post-stapedotomy state, *Procedia IUTAM*, 24, 48-63, 2017. DOI: <u>10.1016/j.piutam.2017.08.042</u>.
- Lesiak P. et al.: Three-dimensional-printed mechanical transmission element with a fiber bragg grating sensor embedded in a replaceable measuring head. Sensors, Multidisciplinary Digital Publishing Institute, 22, 9, 1-13, 2022. DOI: 10.3390/s22093381.
- 12. Marek P., Pawlicki J., Mościcki A.: Tightness problems at the flange connection in transient temperature and high pressure condition. *Engineering Failure Analysis*, 133, 105986, 2022. DOI: <u>10.1016/j.engfailanal.2021.105986</u>.
- 13. Mościcki A., Pawlicki J., Głowacki D., Suprynowicz K.: Limit load and failure mechanisms of soda lime glass foam. *Journal of Materials Science*, 1-12, 2018. DOI: <u>10.1007/s10853-018-2790-6</u>.
- Pawlicki J., Głowacki D., Zwoliński J., Mościcki A.: Elastic limit load resource when reaming holes in turbine rotor discs. *Engineering Failure Analysis*, 113, 104555, 2020. DOI: <u>10.1016/j.engfailanal.2020.104555</u>.
- 15. Petrus M. et al.: Modelling and characterisation of residual stress of SiC-Ti3C2Tx

MXene composites sintered via spark plasma sintering method. *Materials*, 15, 3, 1175. DOI: <u>10.3390/ma15031175</u>.

- 16. Rogowski K., Pawlicki J.: Numerical analysis of the steam flow past the turbine blade stage. *Journal of Machine Engineering, NOT*, 17, 2, 102-110, 2017.
- Sałaciński M. et al.: Technological Aspects of a reparation of the leading edge of helicopter main rotor blades in field conditions. *Applied Sciences-Basel*, 12, 9, 4249,2022. DOI: <u>10.3390/app12094249</u>.
- Sienkiewicz M., Krzesiński G., Marek P. et al.: FEM Modeling of the Delamination Process in Fabric Composites. *Materials Research-Ibero-american Journal of Materials*, 23, 3, e20190675, 2020. DOI: <u>10.1590/1980-5373-mr-2019-0675</u>.
- Zielaskowski M., Bielecki M., Pawlicki J.: Influence of material heat treatment on low cycle fatigue of austenitic steel at working conditions of gas turbine exhaust structures. *Inżynieria Materiałowa, Wydawnictwo SIGMA-NOT*, 40, 5, 9-17, 2019. DOI: <u>10.15199/28.2019.5.2</u>.
Project within Regional Operational Funds of Mazowian Voivodeship lounched in 2019

"Implementation and training field Przasnysz" Airfield Sieraków



